

 \odot

LNX-0702C-SFP Series

7-Port Industrial Gigabit Unmanaged Ethernet Switch, with 5*10/100Tx + 2*100/1000 SFP Slot




Features

- ► Supports 5-Port 10/100Tx and 2-Port 100/1000 SFP slots
- ► Supports Auto MDI/MDI-X Function
- Store-and-Forward Switching Architecture
- ► 5.0Gbps Back-Plane (Switching Fabric)
- ► 8K MAC Address Table
- ► Surge Protection: 2,000 VDC Support
- ► ESD Protection: 6,000 VDC Support
- ► Redundant Power Input Design: 12~48VDC
- ► Built-in 1 Relay Output for Power Failure Warning
- ► IP30 Rugged Metal Case Design
- ► DIN-Rail and Wall Mount Support
- ▶ Operating Temperature Range STD: -10° to 70°C, EOT: -40° to 75°C
- ► 5-Year Warranty

INTRODUCTION

Antaira Technologies' LNX-0702C-SFP series industrial gigabit unmanaged Ethernet switch features five 10/100Tx ports and two dual rate 100/1000Fx SFP slots. This product series support wide range power input from 12 to 48VDC, and provides high EFT and ESD protection to protect against unregulated voltage. It also provides wide operation temperature models for standard: -10° to 70°C and extended: -40° to 75°C. The LNP-0702C-SFP series is an ideal solution for harsh environment and industrial applications.

DIMENSIONS



Toll-Free:1 (844) 268-2472

T: 1 (714) 671-9000

F: 1 (714) 671-9944



SPECIFICATIONS

Technology	
Standards	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3az Gigabit Fiber
Processing Type	Store and Forward
Protocol	CSMA/CD
Flow Control	IEEE 802.3x back pressure flow control
Switch Properties	
Switch Architecture	Back-Plane (Switching Fabric): 5.0Gbps
Transfer Rate	14,880pps for Ethernet Port 148,800pps for Fast Ethernet Port
Broadcast Storm Rate Limit	CSMA/CD
Memory Buffer	7,926pps (default)
Jumbo Frame	-
MAC Table Size	8K
Interface	
Ethernet Port	5*10/100Tx Fast Ethernet
Fiber Port	2*100/1000 SFP Slot
Network Cable	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5
Power Requirements	
Input Voltage	12~48VDC, Redundant Input
Overload Current Protection	Present
Connection	1 removable 6-contact terminal block
Reverse Polarity Protection	Yes
Power Consumption	6W

Mechanical Characteri	stics
Housing	Metal, IP30 protection
Dimensions	30 x 99 x 142 mm (W*D*H)
Weight	Unit: 1.3 lbs. Shipping Weight: 1.7 lbs.
Mounting	DIN-Rail, wall mounting (optional)
Environmental Limits	
Operating Temperature	STD: 0° to 70°C EOT: -40° to 75°C
Storage Temperature	-40°C ~ 85°C
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Class A
EMS	EN6100-4-2,3,4,5,6,8, EN6100-6-2,4
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE, UL 61010-1, UL 61010-2-201, UL Class 1 Division 2, ISA 12.12.01
Warranty	5 Years

ORDERING INFO

LNX-0702C-SFP	7-Port Industrial Gigabit Unmanaged Ethernet Switch, w/ 5*10/100Tx, and 2*100/1000 SFP Slot
LNX-0702C-SFP-T	7-Port Industrial Gigabit Unmanaged Ethernet Switch, w/ 5*10/100Tx, and 2*100/1000 SFP Slot; EOT: -40° to 75°C
Optional Accessories	
MDR-10-12	10W Industrial Din Rail Power Supply, 12VDC
MDR-20-24	20W Industrial Din Rail Power Supply, 24VDC
MDR-40-48	40W Industrial Din Rail Power Supply, 48VDC
MDR-60-49	60W Industrial Din Rail Power Supply, 48VDC

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by ANTAIRA manufacturer:

Other Similar products are found below:

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03

HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A
CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C

E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M

NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K

26546803 26546805 26546831 CJ1W-OD204