MSSA Series

Microminiature Slide Switches

| | SPECIFICATIONS | | FEATURES | |
|----------------------------------|---|-----------|---|--|
| SUBJECT TO CHANGE WITHOUT NOTICE | Contact ratings: Gold; 0.4 Volt-Amps (VA) max. at 20 V max. (AC or DC) Silver; 100 mA at 125 VAC or 30 VDC Initial contact resistance: 30 milliohms max. Insulation resistance: 100 megohms min. at 250 VDC Dielectric strength: 250 volts RMS at sea level Electrical life: 10,000 cycles min. Operating temperature range: -10°C to +60°C Actuation force: 250g ± 150g Solder heat resistance: 260°C max. for 3 seconds | | Low Profile. Epoxy sealed terminals. Cosmetic molded case. | |
| | | | MATERIALS Contacts & terminals: Gold or silver avail Housing and Actuator: Thermoplastic Base: High temperature thermoplastic | able (see contact ratings) |
| SPECIFICATIONS SUBJ | MODEL NO. PLATING MSSA22G GOLD | 2P2T | Terminal seal: Epoxy .098 (2.50) TRAVEL/THROW .217 [5.50] | .079 [2.00] |
| SPE | | | 2.00]157 [4.00]197 [5.00] + .098 [2.50]035 [.90] DIA. 6 PLCS | |
| Ĺ | VERTICAL ACTUATOR | SCHEMATIC | MECHANICAL OUTLINE | P.C. BOARD LAYOUT |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Slide Switches category:

Click to view products by Apem manufacturer:

Other Similar products are found below:

6-1437581-1 M43R MHS123K15D MHS133K MHSS1104A MMD GH49S010001 MSS12A EPS1PC1 1825074-1 1825160-3 1825167-2 1825289-7 K232CB 25139NLDB 25449NAH SLB1240R45 1825078-1 1825080-4 1825269-1 1825270-2 STS141RA04 T2215BEN506 GH46P000001 GH46W000001 GH49P010001 25339NA M42A TG36P000000 TG36P000050 AYZ0202AG 47227LFE 49331L 50208L L203091MS02Q 4-1437581-7 X2225CR-437W 49329L 1101M1S3ZB8E2 1-1437581-1 MSS2225G04 TG39W000000 1825075-1 MSS42G TG36WS80065 T105S1CWZBE SLB124145 SLB1280R5 SLB1340R45 25136NLDB