


**NOTES:**

1. Unless otherwise noted, all dimensions are in inches.
2. Break all sharp edges, de-burr & remove loose chips.
3. Material: Copper (AAVID Thermalloy #573400d00000)
4. Solderable finish
5. Mark with contrasting ink as shown, if specified by P.O.
6. Approximate Weight: 0.2 oz [6g]
7. Thermal rating: 20°C/W

TOLERANCES - UNLESS OTHERWISE SPECIFIED						TITLE: <b>SMT HEATSINK</b>		MODEL: <b>HS24</b>	
.XX = ±.01 [.254] .XXX = ±.005 [.127] ANG. = ±5°						SUBJECT: <b>MECHANICAL DRAWING</b>			
ENGINEER: <b>AOL</b>	DRAWN BY: <b>J.FAY</b>	DCAL: <b>14040</b>	SH. <b>1</b> OF <b>1</b>	FILENAME: <b>HS24</b>	REV: <b>E</b>	DATE: <b>24MAR14</b>			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Heat Sinks](#) category:*

*Click to view products by [Apex Microtechnology](#) manufacturer:*

Other Similar products are found below :

[581102B00000G](#) [656-15ABPE](#) [657-20ABPNE](#) [7020B-TC12-MTG](#) [73452PPBA](#) [7G0011A](#) [PF720G](#) [A22-4026](#) [120-1873-007](#) [HAH10L](#)  
[HAH15L](#) [HF20](#) [1542616-1](#) [HS-2506-F1](#) [HS-87M0-F2](#) [218-40CTE3](#) [231-69PAB-15V](#) [25-7520](#) [SW50-4G](#) [231-75PAB-13V](#) [231-75PAB-](#)  
[15V](#) [253-122ABE-22](#) [PSC22CB](#) [CLP212SG](#) [CLP-7701G](#) [HAA083](#) [HAF10L](#) [HAQ10T](#) [D10100-28](#) [TO5-002D](#) [BDN183CBA01](#) [3-21053-4](#)  
[32438](#) [TX0506-1B](#) [TX1806B](#) [LAE66A3CB](#) [WA-DT2-101E](#) [511-3U](#) [73381PPBA](#) [73403PPBA](#) [7G0047C](#) [COMX-440-HSP](#) [510-12M](#)  
[D10650-40T5](#) [V8511 Y](#) [APF40-40-13CB/A01](#) [780653U04500G](#) [ATS-54310K-C2-R0](#) [FK 216 CB SA](#) [FK 231 SA 220](#)