

WAD101N

Product no.: WAD101N



Benefits





Technical Data

Dimensions L x W x H (mm)	175 x 135 x 102
Dimensions L x W x H (inches)	6,89 x 5,31 x 4,02
Weight (approx.) in kg	2.4
Voltage	120 V / 60 Hz
Power	105 W
Channels	1
Temperature range (depends on tool) °C	50 - 450 (550)
Temperature range (depends on tool) °F	122 - 842 (999)
Temperature accuracy °C	± 9 (30)
Temperature accuracy °F	± 17 (50)
Temperature stability °C	± 2
Temperature stability °F	± 5
Equipotential bonding socket	Via a 3.5 mm jack bush (initial state-hard-grounded)
Display	---
Air consumption l/min	10
Operating pressure in bar/psi	4/58
Capacity l/min	max. 10
Vacuum	---

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Soldering & Desoldering Stations](#) category:

Click to view products by [Apex Tool Group](#) manufacturer:

Other Similar products are found below :

[GS1116](#) [BH-010](#) [T0058768747](#) [CA0202](#) [CA0201](#) [MFR-CA3](#) [WXD2N](#) [Q-7100-9000](#) [T0058757898](#) [WXD2010N](#) [T0058768762](#) [145-2000-ESDN](#) [T0058758721N](#) [WTL1000-1](#) [700-3051-ESD](#) [0051514699N](#) [0051512199N](#) [T0058768725N](#) [MT-688](#) [202485](#) [ZD-415R](#) [ZD-415R-H](#) [WELPB102](#) [HR-2550A](#) [T130-1.0I](#) [T0051011299N](#) [857DW+](#) [ECC92420EU](#) [850A+](#) [ECC168808EU](#) [BST-S-120](#) [9SS-968B-HG](#) [5SS-554-POT](#) [5SS-553-POT](#) [5SS-554-H](#) [5SS-553-H](#) [5PK-366NA-T](#) [5SS-552-POT](#) [5SS-551-POT](#) [5SS-552-H](#) [5SS-551-H](#) [508-366A-T](#) [508-366D-T](#) [5SS-331N1-H](#) [5SI-131-H](#) [5SI-131-3.2D](#) [5SI-131-I](#) [CVC-7CN0004P](#) [CVC-8CH0010S](#) [CV-H5-DSHP](#)