

Description

The 1240i is a low cost, programmable step motor driver, suitable for a wide range of motion control applications. It includes a sophisticated controller integrated with a 50 watt microstepping amplifier.

The 1240i includes Applied Motion's easy to use $Si\ Programmer^{TM}\ Windows\ software for the rapid development of stand alone motion control programs. The 1240i can also be commanded in real time from a host PC or PLC, using the SiNet Command Language^{TM}.$

For multi-axis applications, up to eight 1240i drives can be networked using the SiNet Hub-8. The hub also allows the 1240i to be mixed with any of the other six Si[™] drive models, fulfilling the exact requirements of your application at the lowest possible cost.

The 1240i includes 8 programmable inputs for triggering, branching, position sensing and end of travel detection. 3 programmable outputs can send signals to other electronic devices and activate relays.

Features


- Can be programmed for stand alone operation with the easy to use Si Programmer™
 Windows software (software and programming cable included).
- Can be operated in real time from a host PC or PLC using the SiNet Command Language™.
- Requires 12 42 VDC power supply, up to 1.5 A.
- Programmable motor current: up to 1.2 amps/phase.
- Microstepping: 2,000 50,800 steps/rev.
- Speeds to 50 rev/sec.
- 20 kHz PWM amplifier with mixed fast/slow decay.
- 8 optically isolated 5 24 V inputs can be configured for sinking or sourcing logic.
- 3 optically isolated outputs, 30 VDC, 100 mA.
- · Automatic idle current reduction.
- Drives 4, 6 or 8 lead step motors, sizes 11 23.
- Compatible step motors available from stock.
- Compact size (0.7 x 3.0 x 4.0 inches).
- Four .156 inch mounting holes, 2.7 x 3.7 inch spacing.
- Screw terminal connectors.


Recommended Motors


| PART NO. | SIZE | WINDING CONNECTION | CURRENT | TORQUE |
|----------|----------------|--------------------|---------|-----------|
| HT11-012 | 1.10 sq x 1.32 | series | 1.0 A | 7 oz-in |
| HT11-013 | 1.10 sq x 1.87 | series | 1.0 A | 15 oz-in |
| 5014-842 | 1.38 sq x 1.57 | series | 1.0 A | 26 oz-in |
| HT17-068 | 1.65 sq x 1.30 | parallel | 1.2 A | 22 oz-in |
| HT17-072 | 1.65 sq x 1.54 | parallel | 1.1 A | 36 oz-in |
| HT17-076 | 1.65 sq x 1.85 | parallel | 1.1 A | 44 oz-in |
| HT23-393 | 2.22 sq x 1.54 | parallel | 1.2 A | 54 oz-in |
| HT23-396 | 2.22 sq x 2.13 | parallel | 1.2 A | 125 oz-in |
| HT23-399 | 2.22 sq x 2.99 | parallel | 1.2 A | 187 oz-in |

Torque Curves


24 Volt Power Supply









40 Volt Power Supply







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Motor Drives category:

Click to view products by Applied Motion manufacturer:

Other Similar products are found below:

GMA02 R7DBP02L 1300920283 ST10-S GMA11 GMA20 R88DUA03LAAC100V30W R88DUA12HA R88DUP03LAAC100V30W STR2 VFD002EL11A MFMCB0030GET MFECA0030EAM 1302263150 1300920078 R88D-GT04H R88D-GN04H-ML2 R7D-BP01H R88D-KN04L-ECT 70354063 79294435 27358015 15275008 ST5-Q-EN 1SFA896103R1100 1SFA896103R7000 1SFA896112R1100 R88D-GP08H GNCF8-11 KLC35BE ST10-Q-RN 1302263161 SV2D10-Q-AE VX5A1300 R88A-CA1C005SF-E R88A-CR1B005NF-E SEH 71-4B U-PKZ0(400V50HZ) LUCC12BL LUCC12FU LU9BN11L LULC08 GV2P01 UDS1UR6M50CANCZ183 LC1D09M7 103H7126-1740 103H7823-1741 111.3761.20.00E 111.3761.30.00E 808070RAT250