# Toggle Switches



Well known for their quality and reliability, Bulgin's toggle switches are cost effective solutions to many existing applications. These switches offer features at an attractive price point often well below that of the existing competition.

- O Nylon and Metal switch variants
- Multiple Lever Options
- Ratings up to 20A, 250V ac 277V ac
- IP67 panel seal versions, supplied complete with gaskets (3900 Series – All Variants)
- O Single and double pole
- Choice of circuit options including 3 position and momentary
- Mounting hole: 12.7mm diameter.
- Sealing accessories available
- Quick Connect, Solder, Screw and PCB Termination Options





# 3900 Metal Toggle Switches 16A 250Vac - IP67 Sealed Versions





### **Key Features**

- Metal toggle switches
- Ratings up to 20A, 277V ac
- Single and double pole
- Choice of circuits including 3 position and momentary
- Sealed version supplied complete with gaskets
- O Panel seal version to IP67
- 0 6.3mm terminals
- Guard option

Terminal	Function		Actuator	Body	Options
C 10.5 6.3 x 0.8	3900 ON - OFF 3901 ON - OFF (momentary ON) ↑ → 3902 ON - OFF	Double Pole  3950 ON - OFF  3951 ON - OFF  (momentary ON)  1:::: 3952 ON - OFF	Metal toggle finish is nickel plate	Single pole Thread: 15/32" x 32TFI Keyway  17.5 10.5 17.0  Panel sealed, single pole Thread: 15/32" x 32TFI Keyway  Panel sealed, single pole Thread: 15/32" x 32TFI Keyway	Neck Seal M539 Actuator is visible  Cover M1080  Covers have internal nylon nuts M1080-2
Screw & Clamp	3910 ON - ON 3911 ON - ON (momentary 1 side) 13920 ON - OFF - ON μ	(momentary OFF)    3960 ON - ON   3961 ON - ON (momentary 1 side)   3970 ON - OFF - ON µ   11111111111111111111111111111111111	Metal toggie finish is nickel plate	Double pole, without barrier Thread: 15/32* x 32TPI Servery 17.5 10.0 30.6  B Double pole, with barrier Thread: 15/32* x 32TPI Koyvery	Covers have internal metal hex nuts  Fixing nuts Nickel plated brass are supplied  14.0
o 3.1 Solder	3921 ON - OFF - ON μ (momentary 1 side)  1 · · · · ·  3922 ON - OFF - ON μ (momentary 2 sides)  1 · · · · · 1	3971 ON - OFF - ON μ (momentary 1 side)  1 3972 ON - OFF - ON μ (momentary 2 sides)  1 1 1 1	Metal toggle finish is nickel plate  Metal toggle finish is nickel plate  Metal toggle finish is nickel plate	Panel sealed, double pole, with terminal barrier  Thread: 15/32" x 22TPI  Keyway  17.5 10.0 31.1  Switches with F toggles have double pole bodies, regardless of circuit  Panel sealed, double pole, without terminal barrier  Thread: 15/32" x 22TPI  Keyway  17.5 10.0 31.1	Plate P236 Plate SP or DP



#### **Approvals and specifications**

W UL/CSA Ratings 3901, 3902, 3920, 3921, 3922 16A, 277Vac 1 HP, 250Vac

**91 ©** 7A, 72Vdc 14A, 36Vdc

> 3910, 3901, 3952, 3960, 3961, 3970, 3971, 3972 16A, 277Vac 1 HP, 250Vac 1/2 HP, 125Vac 7A, 72Vdc 14A, 36Vdc

3900, 3950 20A, 277Vac 1 HP, 250Vac 1/2 HP, 125Vac 7A, 72Vdc 14A, 36Vdc

ENEC Ratings 3900, 3901, 3902, 3950, 3952, 3960, 3961 16(4)A 250Vac

3910, 3911, 3920, 3921, 3922, 3951, 3970, 3972 10 4)A 250Vac

Approvals and ratings vary with function. 3mm contact gap except where marked  $\boldsymbol{\mu}.$ 

\* CSA approval for A and B bodies only

#### **Dimensions** mm) \* Indicates ON position (for ON - OFF switches)


#### Single pole

(C terminals shown)














(C terminals shown with barrier)




Double pole





#### Toggle Switch - sealed version

BE and BF types







#### **Examples**









C3920BA - - -



C3950BF - - -



☑ C3972BB - - -





#### **Key Features**

- Nylon toggle switches
- Ratings up to 20A, 250V ac
- O Single and double pole
- Wide choice of terminals
- Choice of circuit options including 3 position
- Flat & round actuator options

#### **Approvals and specifications**

4 16(4)A 250Vac T85

UL 20A 250Vac Non Ind (Single pole)
UL 16A 250Vac Non Ind (Double pole)
UL CSA (2 pos types) 250Vac 1hp, 125Vac 1/2hp
UL CSA (3 pos types) 250Vac 1/2hp, 125Vac 1/4hp
CSA 16A 250Vac Non Ind
UL 85°C, file E45221, CSA file LR10990
UL and CSA N/A on momentary types

Selective "A, B, C" and "OFF, A, A+B" circuits at 5 amp also available. 3mm contact gap except where marked  $\mu$ .

Terminal	Function	Actuator	Body	Options
C	Single Pole Double  1700 ON - OFF ON - OFF	Pole 16.4	O Single pole  Thread: 15/32" x 32TPI  Keyway  10.0 12.2	Neck Seal M539  Material - Nitrile (H & R Actuators) Actuator visible  Cover M1080  Material - EPDM (R Actuator only)
K 2.0 7 9.1  T	1710 μ 1760 ON - ON	<b>R</b>	Double Pole Thread: 15/32* x 32TPI  Keyway  10.0  1.3  012.7	Cover M531  Material - PVC (R Actuator only)  Covers have internal nylon nuts  Fixing nuts (Standard is M506 & T92)
X 4.0 1 9.1	1721 μ ON - OFF - ON μ (momentary 1 side)	The switch is on	Panel hole (all types) Panel thickness (Max) Both nuts - 3.5mm Less backnut - 6.5mm	T5 Hex brass M506 Hex nylon  T92 Knurled brass - 16.2
	1722 ON - OFF - ON µ (momentary 2 sides)	between centre terminals (2 & 5) and the terminals over which the lever is positioned.		Plate P236 Plate SP or DP



**Dimensions** mm) \* Indicates ON position (for ON - OFF switches)

#### Single pole

(C terminals shown)







Optional F00232PAAA plate SP or DP

#### Double pole

(C terminals shown)





Without barrier



#### **Examples**









C1700R - -

C1700H - -

C1760R - -

C1750H - -

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Other Tools category:

Click to view products by Arcolectric manufacturer:

Other Similar products are found below:

CR-05FL7--150R CR-05FL7--698K 899-2-KT46 899-5-KT46 CR-0AFL4--332K CR-12FP4--260R CRCW04021100FRT7

CRCW04021961FRT7 5800-0090 CRCW04024021FRT7 CRCW040254R9FRT7 CRCW0603102JRT5 59065-5 00-8273-RDPP 00-8729-WHPP 593033 593058 593072 593564100 593575 593591 593593 011349-000 CRCW08052740FRT1 LUC-012S070DSM LUC-018S070DSP 599-2021-3-NME 599-JJ-2021-03 00-5080-YWPP 5E4750/01-20R0-T/R LW1A-L1-GL LW1A-P1-GD LW1L-A1C10V-GL LW1L-M1C70-A 0202-0173 00-9089-RDPP 00-9300-RDPP CRCW2010331JR02 01-1003W-8/32-10 601-GP-08-KT39 601-JJ-06 601-SPB 601YSY 602-JJ-03 602SPB 602Z 603-JJ-07-FP 603-JJY-04 604J 604-JJ-05