

ARDUINO YÚN REV 2

Code: ABX00020


The Yún Rev 2, Linux powered board with the Arduino simplicity, is the perfect board for your IoT projects!



The Yún rev. 2 with the power of a Linux based system that enables advanced network connections and applications.

Connection to your WiFi or wired network is simple thanks to the Yún Web Panel and the dedicated "YunFirstConfig" sketch. The Web panel allows you to manage your shield preferences and upload your sketch. The Yún rev. 2 uses the Bridge library and so extends the board capabilities by using the Linux processor. As always, every element of the platform – hardware, software and documentation – is freely available and opensource. This means that you can learn exactly how it's made and use its design as the starting point for your own projects.





AVR Arduino microcontroller

Microcontroller ATmega32U4

Operating Voltage 5V
Input Voltage 5V
Digital I/O Pins 20
PWM Output 7
Analog I/O Pins 12

DC Current per I/O Pin 40 mA on I/O Pins; 50 mA on 3,3 Pin

Flash Memory 32 KB (of which 4 KB used by bootloader)

SRAM 2.5 KB EEPROM 1 KB Clock Speed 16 MHz

Linux Microprocessor

Processor Atheros AR9331


Architecture MIPS Operating Voltage 3.3V

Ethernet 802.3 10/100Mbit/s WiFi 802.11b/g/n 2.4 GHz

USB Type 2.0 Host
Card Reader Micro-SD
RAM 64 MB DDR2

Flash Memory 16 MB Clock Speed 400 MHz





Compatibility

The Yún Rev. 2 board allows you to connect to the internet using the onboard WiFi or Ethernet connection. Furthermore thanks to the Bridge library it able to extend the functionalities of the Microprocessor by using the computational power of the Linux processor on the shield. Using the Yún Web Panel it is also possible to configure all the shield-related features and remotely upload sketches on the board connected to the shield.

On-board Indicators

The shield contains a number of signalling LEDs:

- ON (green): indicates that the shield is properly powered
- WLAN (blue): indicates a connection to a wireless network
- WAN (red): indicates connection to ethernet
- USB (white): indicates system activity and/or if a USB key is mounted

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Networking Development Tools category:

Click to view products by Arduino manufacturer:

Other Similar products are found below:

MAX79356CAEVK1# MAX2982EVSYS BASENODE-EK DC-ME-9210-LX WIZ550SR-EVB DC9007A DC9021B

ATPANCOORDINATOR-EK SM2400-EVK2M2-C SM2400-EVK2M5-A Pi01-2 Pi01-3 Pi01-4 Pi01-42 Pi01-43 pind-4ge pind-4ga tbit32 DC9020B DC9022B RAPID-TSNEK-V0001 ABX00017 GKX00006 DC-ACC-DBME DC-ME-01T-MF-10 DG-EXT-300-RR

XP10010NMK-01 XPC100100K-02 XPC240300EK XPC250300EK XPE200100EK Development Kit, RS232 Development Kit, USB

MAX11947EVKIT# RD-HNPH2DCP962KIT-01 ATPL360-EK MIKROE-3739 MIKROE-3888 MIKROE-2747 NNDK-MOD5213-KIT

SB800EX-KIT ESP32-GATEWAY NCN5110ASGEVB NCN5121ASGEVB FPWEB2 ARGNKIT XENNKIT 604565285904 110060622

110060623