Arduino Nano ESP32

Product Page

Short Description

The new member to our iconic Nano family, the Nano ESP32. This board brings all the power of the well-known ESP32-S3 with the full support of the Arduino ecosystem, allowing makers to explore the world of Arduino and MicroPython without any blocker. Just unleash your creativity and start building for the next IoT project.

Overview

Introducing the Nano ESP32, a powerful addition to the Arduino ecosystem that brings the popular ESP32-S3 to the world of Arduino and MicroPython programming. Whether you're a beginner stepping into the world of IoT or MicroPython, or an advanced user looking to incorporate it into your next product, the Nano ESP32 is the perfect choice. It covers all your needs to kick-start your IoT or MicroPython project with ease.

Let's explore the key features of the Nano ESP32:

- **Tiny footprint:** Designed with the well-known Nano form factor in mind, this board's compact size makes it perfect for embedding in standalone projects.
- **Wi-Fi and Bluetooth**[®]: Harness the power of the ESP32-S3 microcontroller, well-known in the IoT realm, with full Arduino support for wireless and Bluetooth[®] connectivity.
- Arduino and MicroPython support: Seamlessly switch between Arduino and MicroPython programming with a few simple steps. We even offer an introductory course for those new to the MicroPython world, find more information in the documentation page.
- **Arduino IoT Cloud compatible:** Quickly and easily create IoT projects with just a few lines of code. Our setup takes care of security, allowing you to monitor and control your project from anywhere using the <u>Arduino IoT Cloud app</u>.

• **HID support:** Simulate human interface devices, such as keyboards or mice, over USB, opening up new possibilities for interacting with your computer.

There are no more excuses to delay your exploration of IoT and MicroPython. The Nano ESP32 provides everything you need to start creating and discovering the endless possibilities.

Tech Specs

Board	Name	Arduino® Nano ESP32
	SKU	ABX00083 / ABX00092
Microcontroller	u-blox® NORA-W106 (ESP32-S3)	
USB connector	USB-C®	
Pins	Built-in LED Pin	13
	Digital I/O Pins	14
	Analog input pins	8
	PWM pins	5
	External interrupts	All digital pins
Connectivity	Wi-Fi®	u-blox® NORA-W106 (ESP32-S3)
	Bluetooth®	u-blox® NORA-W106 (ESP32-S3)
Communication	UART	1x, D0 (TX), D1, (RX)
	I2C	1x, A4 (SDA), A5 (SCL)

	SPI	D11 (COPI), D12 (CIPO), D13 (SCK). Use any GPIO for Chip Select (CS).
Power	I/O Voltage	3.3 V
	Input voltage (nominal)	5-18 V
	Source Current per I/O Pin	40 mA
	Sink Current per I/O Pin	28 mA
Clock speed	Processor	up to 240 MHz
Memory	ROM	384 kB
	SRAM	512 kB
	External Flash	128 Mbit (16 MB)
Dimensions	Width	18 mm
	Length	45 mm

Logistics

Weight

0.03 kg

Dimensions

8 cm x 5.8 cm x 2.3 cm

FAQ (Pre-sales)

Is the Nano ESP32 compatible with MicroPython?

Absolutely! This board fully supports MicroPython. For detailed information on setting it up and getting started with MicroPython, please visit <u>docs.arduino.cc/nano-esp32</u>.

How can I power the Nano ESP32?

The Nano ESP32 can be powered in two ways. Firstly, you can power it via the USB port, which activates the VBUS pin as an output. Alternatively, you can supply power through the VIN pin, accepting an input voltage range of 5 to 18 Volts.

Does it use the official ESP32 core?

Yes, if you are an ESP32 user, simply upload the latest version of the ESP32 core through the board manager in the Arduino IDE. For more information, please refer to the <u>official</u> <u>documentation page</u>.

Will the Nano ESP32 be compatible with sketches from generic ESP32 boards?

The Arduino Nano ESP32 can run code written for other ESP32 devices without any fuss. It's designed to be fully compatible with the ESP32 ecosystem, making it easy to port existing code.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multiprotocol Development Tools category:

Click to view products by Arduino manufacturer:

Other Similar products are found below :

CYW94343WWCD1_EVB ABX00083 ABX00092 ABX00087 XKC-M5T-W ATWINC3400-XPRO 2636 STEVAL-FKI001V1 TEL0111 ATWINC3400-XSTK RE-WFKIT-9260NVP 2542 irpi01-868 BCM94343WWCD1_EVB DFR0505 XK3-C-A2-UT-U XKC-V1T-U ESP32-S3-EYE ISM43340-L77-EVB ISP4520-AS-DK 453-00010-K1 453-00011-K1 XPC270300EK MIKROE-2440 MIKROE-4493 MTDOT-BOX-G-868-B MTDOT-BOX-G-915-B LBEH5DU1BW-TEMP-DS-SD NRF5340-DK 113990254 SIMSA868C-Cloud-DKL SIMSA868-Cloud-DKL SIMSA915-Cloud-DKL SIMSA-DKL SKY66420-11EK1