

# POWER

## LCB150

### 150 Watt Single Output Power Supply

#### Data Sheet

**Total Power:** 150 W  
**# of Outputs:** Single  
**Outputs:** 5 - 48 V

#### SPECIAL FEATURES

- No-load power consumption 1.5 W
- Low cost
- 3.9" x 7" x 1.5"
- 10% output voltage adjust
- -25 °C to 70 °C with derating
- High efficiency: 90% @ 230 Vac
- Power ON with LED indicator
- Withstand 2G vibration test
- Two year warranty

#### COMPLIANCE

- EMI Class B
- EN61000, EN61204-3

#### SAFETY

- UL, cUL 60950-1
- TUV 60950-1
- CE



#### Electrical Specifications

Input	
Input range	88 - 132 Vac, 176 - 264 Vac (by switch) 248 - 373 Vdc
Frequency	47 - 63 Hz, Nominal 50/60
Inrush current	50 A, cold start at 25 °C, 230 Vac
Harmonics	EN61000-3-2: 2000 Class A, EN61000-3-3: 1995+A1:2001
Input current	3 A / 115 Vac
Hold up time	>25 ms
Efficiency	90% typical at full Load / 230 Vac nominal
Leakage current	< 2 mA at 264 Vac
Isolation	Isolation: PRI-Chassis 1500 Vac PRI-SEC 3000 Vac SEC-Chassis 500 Vac

## Electrical Specifications

Output		
Output rating	See ordering information	90 - 264 Vac
Output tolerance	± 1% to 2%	90 - 264 Vac
Total regulation range	± 0.5% to 1%	Combined line/load/transient when measured at output terminal
Rated load	90 - 158.4 W	Derate linear to 50% from 50 °C to 70 °C
Output noise (PARD)	100 - 200 mV p-p	Main output Measured with a 0.1 µF Ceramic and 10 µF Tantalum Capacitor on any output, 20 MHz
Output voltage overshoot		No overshoot/undershoot outside the regulation band during on or off cycle
Short circuit protection	Protected, no damage to occur	Bounce mode
Output isolation		Standard per safety requirements
Overload protection (OCP)	>105% rated output power	Main output
Overvoltage protection (OVP)	115% to 150%	Main output
Output voltage adjust	± 10%	Main output

## Environmental Specifications

<b>Operating temperature</b>	-25 °C to +70 °C, linear derating to 50% from 50 °C to 70 °C
<b>Storage temperature</b>	-40 °C to +85 °C
<b>Humidity</b>	20 to 90%, non-condensing
<b>Vibration</b>	10 - 500 Hz, 5G 10 min/1 cycle, period for 60 min each along X, Y, Z axes

## Ordering Information

Model Number	Output Voltage	Output Current	Vo Adjust	Output Power	Efficiency
LCB150E	5 V	18 A	± 10%	90 W	83%
LCB150L	12 V	12.5 A	± 10%	150 W	88%
LCB150N	15 V	10 A	± 10%	150 W	89%
LCB150Q	24 V	6.5 A	± 10%	156 W	90%
LCB150W	48 V	3.3 A	± 10%	158.4 W	90%

## Miscellaneous Specifications

### BURN-IN

100% Burn-in at 45 °C, at full load. Duration of burn-in determined by Quality Assurance Procedures.


### MTBF

The power supply has a minimum MTBF of 244K hours according to MIL-HDBK-217F.

### WARRANTY

Artesyn Embedded Power shall warrant the power supply to be free of defects in materials and workmanship for a minimum period of two years from the date of shipment, when operated within specifications. The warranty shall be fully transferable to the end owner of the equipment powered by the supply.

Mechanical Drawings



WORLDWIDE OFFICES

**Americas**

2900 South Diablo Way  
Suite B100  
Tempe, AZ 85282, USA  
+1 888 412 7832

**Europe (UK)**

Ground Floor Offices, Barberry House  
4 Harbour Buildings, Waterfront West  
Brierley Hill, West Midlands  
DY5 1LN, UK  
+44 (0) 1384 842 211

**Asia (HK)**

14/F, Lu Plaza  
2 Wing Yip Street  
Kwun Tong, Kowloon  
Hong Kong  
+852 2176 3333

**ARTESYN™**  
An Advanced Energy Company

[www.artesyn.com](http://www.artesyn.com)

Artesyn Embedded Technologies, Artesyn Embedded Power, Artesyn, and all Artesyn related logos are trademarks and service marks of Artesyn Embedded Technologies, Inc. All other names and logos referred to are trade names, trademarks, or registered trademarks of their respective owners. Specifications are subject to change without notice. © 2019 Artesyn Embedded Technologies, Inc. All rights reserved. For full legal terms and conditions, please visit [www.artesyn.com/legal](http://www.artesyn.com/legal).

For more information: [www.artesyn.com](http://www.artesyn.com)  
For support: [productsupport.ep@artesyn.com](mailto:productsupport.ep@artesyn.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Switching Power Supplies](#) category:*

*Click to view products by [Artesyn Embedded Technologies](#) manufacturer:*

Other Similar products are found below :

[70841011](#) [73-551-0005](#) [73-551-0048](#) [PS3E-B12F](#) [PS3E-E12F](#) [AAD600S-4-OP](#) [R22095](#) [KD0204](#) [9021](#) [LDIN100150](#) [LPM000-BBAR-01](#)  
[LPX17S-C](#) [EVS57-10R6/R](#) [FP80](#) [FRV7000G](#) [22929](#) [PS3E-F12F](#) [CQM1IA121](#) [40370121900](#) [VI-PU22-EXX](#) [40370121910](#) [LDIN5075](#)  
[LPM615-CHAS](#) [LPX140-C](#) [09-160CFG](#) [70841025](#) [VPX3000-CBL-DC](#) [VI-LUL-IU](#) [LPM000-BBAR-05](#) [LPM000-BBAR-08](#) [LPM124-](#)  
[OUTA1-48](#) [LPM000-BBAR-07](#) [LPM109-OUTA1-10](#) [LPM616-CHAS](#) [08-30466-1055G](#) [08-30466-2175G](#) [08-30466-2125G](#) [DMB-EWG](#)  
[TVQF-1219-18S](#) [6504-226-2101](#) [CQM1IPS01](#) [SP-300-5](#) [CQM1-IPS02](#) [VI-MUL-ES](#) [22829](#) [08-30466-0065G](#) [VI-RU031-EWWX](#) [08-30466-](#)  
[0028G](#) [EP3000AC48INZ](#) [VP-C2104853](#)