

General Features

- High density cell design for ultra low $R_{DS(on)}$
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation
- Special process technology for high ESD capability


Product Summary




V_{DS}	100	V
$R_{DS(on),TYP} @ V_{GS}=10\text{ V}$	3.7	m Ω
I_D	90	A

Application

- Automotive applications
- Hard switched and high frequency circuits
- Uninterruptible power supply



DFN5x6-8L



Absolute Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Condition	Value	Unit
V_{DS}	Drain-Source Voltage		100	V
I_D	Continuous Drain Current ¹	$T_C=25^\circ\text{C}$	90	A
		$T_C=70^\circ\text{C}$	48	A
V_{GS}	Gate-Source Voltage		± 20	V
I_{DM}	Pulsed Drain Current ²	$T_C=25^\circ\text{C}$	360	A
P_D	Total Power Dissipation	$T_C=25^\circ\text{C}$	60	W
T_{STG}	Storage Temperature Range		-55 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature		-55 to 150	$^\circ\text{C}$

**Thermal Data**

Symbol	Parameter	Typ.	Max	Unit
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	--	63	°C/W
$R_{\theta Jc}$	Thermal Resistance-Junction to Case	--	1.3	

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Limit	Min	Typ	Max	Unit
Static Characteristic						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	100	--	--	V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3.0	4	V
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=80V, V_{GS}=0V$	--	--	1	uA
		$V_{DS}=48V, V_{GS}=0V$	--	--	100	
I_{GSS}	Gate -Source Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	--	--	± 100	nA -
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=10V, I_D=20A$	-	3.7	4.5	mΩ
Dynamic Characteristic						
C_{iss}	Input Capacitance	$V_{DS}=40V, V_{GS}=0V, f=1MHz$	--	2890	--	pF
C_{oss}	Output Capacitance		--	881	--	
C_{rss}	Reverse Transfer Capacitance		--	13.2	--	
$t_{d(on)}$	Turn-On Delay Time	$V_{DD}=40V, V_{GS}=10V, R_G=2\Omega, I_D=20A$	--	16	--	nS
t_r	Turn-On Rise Time		--	13	--	
$t_{d(off)}$	Turn-off Delay Time		--	28	--	
t_f	Turn-Off Fall Time		--	7.5	--	
Gate Charge Characteristic						
Q_g	Total Gate Charge	$V_{DD}=30V, V_{GS}=10V, I_D=30A$	--	23	--	nC
Q_{gs}	Gate-Source Charge		--	5.2	--	
Q_{gd}	Gate-Drain Charge		--	7.3	--	
Reverse diode Characteristic						
V_{SD}	forward on voltage	$I_{SD}=20A, V_{GS}=0V$	--	--	1.2	V
t_{rr}	Reverse Recovery Time	$V_R=0V, I_F=20A, DI_F/dt=100A/\mu S$	--	46	--	nS
Q_{rr}	Reverse Recovery Charge		--	182	--	nC

Typical Electrical and Thermal Characteristics (Curves)

Figure 2. Safe operating area




Figure 3. Thermal impedance




Figure 4. Output characteristics




Figure 5. Transfer characteristics




Figure 6. Gate charge vs gate-source voltage




Figure 7. Static drain-source on-resistance




Figure 8. Capacitance variations




Figure 9. Normalized gate threshold voltage vs temperature




Figure 10. Normalized on-resistance vs temperature




Figure 11. Normalized V_{DS} vs temperature






Figure 12. Source-drain diode forward characteristics






Test circuits

Figure 13. Switching times test circuit for resistive load




AM01468v1

Figure 14. Gate charge test circuit




AM01469v1

Figure 15. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 16. Unclamped inductive load test circuit




AM01471v1

Figure 17. Unclamped inductive waveform



AM01472v1


Figure 18. Switching time waveform




AM01473v1

Ordering and Marking Information

Ordering Device No	Marking	Package	Packing	Quantity
ASDM100R045NQ-R	100R045N	DFN5*6-8	Tape&Reel	4000

PACKAGE	MARKING
DFN5*6-8	 <p>AS □□□ → Lot Number 100R045N □□□□ → Date Code</p>

DFN5*6, 8 Leads



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°



IMPORTANT NOTICE

Xi'an Ascend Semiconductor incorporated MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Xi'an Ascend Semiconductor Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Xi'an Ascend Semiconductor Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Xi'an Ascend Semiconductor Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume .

all risks of such use and will agree to hold Ascendsemi Incorporated and all the companies whose products are represented on Xi'an Ascend Semiconductor Incorporated website, harmless against all damages.

Xi'an Ascend Semiconductor Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Xi'an Ascend Semiconductor Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Xi'an Ascend Semiconductor Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

www.ascendsemi.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Ascend](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60_F109](#) [FDZ595PZ](#) [AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#) [BSC884N03MS G](#) [BSF024N03LT3 G](#)
[PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-](#)
[7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#)
[SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#)
[C3M0021120D](#) [DMN13M9UCA6-7](#) [BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IRF40SC240ARMA1](#)
[IPS60R1K0PFD7SAKMA1](#)