



NOTES:
Mechanical:
1. Housing material : Glass Filled Polyester UL94V-0,
Color: Black

2. Contact material: Phosphor Bronze t=0,35mm
3. Contact plating: 6µ" Gold on contact area
100~200µ" Tin on solder area
all over 30~50µ" Nickel
4. Operating Life: 750 Cycles min.
5. PCB Retention Pre-solder: 1 LB min.
6. PCB Retention Post-solder: 10 LBS min.

Electrical:

1. Voltage Rating: 125VAC.
2. Current Rating: 1,5AMP.
3. Contact Resistance: 50mΩ max.
4. Insulation Resistance: 500MΩ min. @ 1000 VDC
5. Dielectric Strength: 1000 VAC RMS 60Hz, 1 min.

Environmental:

1. Storage: -40°C To +85°C
2. Operation: -40°C~+85°C
3. Wave Soldering Temp: 200~220°C(5~10S)
4. Packing: 120pcs/Tray, 2640pcs/Cartron

RoHS compliant
Unit:mm



File No.: E345352

Scale	Free								
TOLERANCE									
XX	±0.20					Drawn	08.07.2009	Dean	
XX	±0.15					Approved	25.08.2015	Amy	
X,XXX	±0.10	③	Update the contact plating	25.08.2015	Amy				
DIM	TOL	②	Update	27.05.2013	Amy				
		①	Drawn	08.07.2009	Dean				
Angle	±5°		Modification						

Customer-No.

ASSMANN WSW-No.

A-200040

Drawing-No.

ASS 0447 CO rev03

Replace

SHEET

1

2

3

4

5

6

7

1

2

3

4

5

6

7

A

B

C

D

E

F

H

G

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [AK-320200-100-S](#) [AK-340305-010-W](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#)
[AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#)
[AK500/16-OE-7-0.5](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AT-K-26-10-W/1000](#) [AWG28-15/G/300](#) [ATUP-P305T](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-330105-300-S](#)
[AK-340406-001-W](#) [A-MCSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-9/G/300](#) [V25HK](#) [A-LED8-1WAAS-MR7-1](#) [AWP2 16-7240](#) [A-2014-0-4-R](#) [DN-91648U](#) [DN-91524U](#)