

NOTES:

Mechanical:

- Housing material : High Temp. Polyester UL94V-0 , Color: Black
- Contact material: Phosphor Bronze t=0.35mm
- Contact plating: Contact area---Selective gold plating
Tails---Tin plated all over 50u" Nickel
- Operating Life: 750 Cycles min.
- PCB Retention Post-solder: 10 LBS min.

Electrical:

- Voltage Rating: 125VAC.
- Current Rating: 1.5AMP.
- Contact Resistance: 35mΩ max.
- Insulation Resistance: 1000MΩ min. @ 500 VDC
- Dielectric Strength: 1000 VAC 60Hz, 1 min.

Environmental:

- Storage: -40°C To +85°C
- Operation: -40°C~+85°C
- IR Reflow Soldering Temp: 255°C~265°C(5~10S)

Packing: 130pcs/Tape reel, 1300pcs/Carton

Order code: A-2004-2-X-LP/SMT

Contact plating:

- Selective 15u" gold
- Selective 30u" gold
- Selective 50u" gold
- Selective 6u" gold

RoHS compliant
Unit:mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	27.05.2013	Amy
X.X	±0.20					Approved	06.04.2017	Amy
X.XX	±0.15							
X.XXX	±0.10	②	Update package qty on page 2	06.04.2017	Amy			
DIM	TOL	①	Add tape reel packing on page 2	22.04.2014	Amy			
		①	Drawn	27.05.2013	Amy			
Angle	±5°	Id.	Modification	Date	Name			

Customer-No.		
ASSMANN WSW-No.		A-2004-2-X-LP/SMT
Drawing-No.		ASS 5696 CO
Replace		rev02
		SHEET 1 / 2



1 2 3 4 5 6 7

A

B

C

D

E

F

G


H

1.PRODUCT 1PCS
 ② 1.SIDE ENTRY SMT 8P8C JACK
 130 PCS/REEL
 1300PCS/CARTON

2.CARTON
 375 580 360
 375 580 360
 Keep each 5pcs blank on front and tail

3.TAPE REEL
 4,0 24,0 24,0

RoHS compliant
 Unit:mm

Scale	Free						Date	Name	Customer-No.	
TOLERANCE							Drawn	27.05.2013	Amy	
X.X	±0.20						Approved	06.04.2017	Amy	
X.XX	±0.15								ASSMANN WSW-No. A-2004-2-X-LP/SMT	
X.XXX	±0.10	②	Update package qty on page 2	06.04.2017	Amy				Drawing-No.	
DIM	TOL	①	Add tape reel packing on page 2	22.04.2014	Amy				ASS 5696 CO	rev02
		①	Drawn	27.05.2013	Amy				Replace	SHEET 2 / 2
Angle	±5°	Id.	Modification	Date	Name					

1 2 3 4 5 6 7

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [A-DF15-HOOD-WP](#) [A-USB-1](#) [AK-320200-100-S](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#) [AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [AWH-24G-E202-IDC](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [AK500/14-OE-5-2](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AK-320400-002-S](#) [AT-K-26-6-B/500](#) [AK-400102-008-R](#) [AT-K-26-6-W/100](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK-340102-010-W](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-310203-018-E](#) [AK-330105-300-S](#) [AK-340406-001-W](#) [A-MCSSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-9/G/300](#)