



**Specification:**

**1. Electrical Char**

Insulation Resistance: 500MΩ min. 500V DC for 1 minute  
 Contact Resistance: 30mΩ max.  
 Rating Current: 1.5A max.  
 Rating Voltage: 150V AC  
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

**2. Physical Char**

Housing: PBT Glass filled (UL 94V-0) Color: Black  
 Soldering Temperature: 235°C for 5 sec.  
 Spring Wire: 0.45mm Dia Phosphor Bronze  
 6u" Gold plating over Nickel  
 Temperature Range: -40°C to +85°C  
 Durability: 750 mating cycles min.

**3. Packing: Tray**

**RoHS compliant**  
 Unit:mm

| Scale     | Free   |     |            |              |            |      |  |  |  |
|-----------|--------|-----|------------|--------------|------------|------|--|--|--|
| TOLERANCE |        |     |            |              |            |      |  |  |  |
| XX        | ±0.20  |     |            |              |            |      |  |  |  |
| .XXX      | ±0.13  |     |            |              |            |      |  |  |  |
| .XXXX     | ±0.05  |     |            |              |            |      |  |  |  |
| DIM       | TOL    |     |            |              |            |      |  |  |  |
| Angle     | +0°30' | Id. | Drawn      | Modification | Date       | Name |  |  |  |
|           |        | ①   | 28.10.2015 |              | 28.10.2015 | Amy  |  |  |  |

| Date       | Name | Customer-No. | Drawing-No.                          | Replace     | SHEET |
|------------|------|--------------|--------------------------------------|-------------|-------|
| 28.10.2015 | Amy  |              | ASSMANN WSW-No.<br>A-2004-3-4-LP-N-R | ASS 7041 CO | rev00 |
| 28.10.2015 | Amy  |              |                                      |             |       |



1 2 3 4 5 6 7

A B C D E F G H

A B C D E F G H

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [assmann](#) manufacturer:*

Other Similar products are found below :

[AU-Y1007-R](#) [AK-320200-100-S](#) [AK-340305-010-W](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#)  
[AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#)  
[AK500/16-OE-7-0.5](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AT-K-26-10-W/1000](#) [AWG28-15/G/300](#) [ATUP-P305T](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-330105-300-S](#)  
[AK-340406-001-W](#) [A-MCSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-9/G/300](#) [V25HK](#) [A-LED8-1WAAS-MR7-1](#) [AWP2 16-7240](#) [A-2014-0-4-R](#) [DN-91648U](#) [DN-91524U](#)