



Material:
 . SPT-1-18AWG(0.824MM²) VW-1 , 105°C 300V
 . Jacket Color: Black
 . All materials must be RoHS compliant.

Electrical :
 . 100% Open & Short Testing
 . Insulation Resistance : 100meg-ohm(Min.)
 . Voltage : 500V DC / 1 Min.

1830±50

RoHS compliant
 Unit: mm

NO.	NAME	QTY	DATE	NAME	SPECIFICATION
①	Cable	1			Power Cord - SPT-1/Open End, Non-Polarized, Unshielded, 105°C, 18AWG 1830MM
			Drawn	Amy	
			Approved	Amy	

Scale	Free	Customer-No.
TOLERANCE		ASSMANN WSW-No.
		AK500-OE-12-NP-6F
DIM	TOL	Drawing-No.
		ASS 8176 CA
Angle	TOL	Replace
		Sheet



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [A-DF15-HOOD-WP](#) [A-USB-1](#) [AK-320200-100-S](#) [AK-330109-020-S](#) [AK-330114-050-S](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#) [AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK-320108-030-S](#) [AK-320200-030-S](#) [AK-330107-010-S](#) [AK-330107-020-S](#) [AK-330505-000-S](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [AWH-24G-E202-IDC](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [AK500/14-OE-5-2](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AK-320100-020-S](#) [AK-320400-002-S](#) [AT-K-26-6-B/500](#) [AK-400102-008-R](#) [AT-K-26-6-W/100](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK-340102-010-W](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#)