



PIN ASSIGNMENT		
P1		P2
1	YELLOW	1
2	BLACK	2
3	BLACK	3
4	RED	4

**Material:**

- Cable: UL1007 18AWG(41/0.16 TC)
  - OD: 2.0MM
- P1 Connector: SATA 15-pin/Female
  - Crimp Type
  - Terminal: 15μ"
  - Insulator: Black PBT
  - PVC 45P Black / Clear HD-PE
- P2 Connector: Big 4Pin Female Housing
  - PH: 5.08MM
  - White
  - Terminal Male, Tin Plated

**Electrical:**

- 100% short, open, miswire test
- Conduct resistance: 3Ω Max.
- Insulation resistance: 20MΩ Min.
- Hi-Pot test: 300V DC



Scale	1:1						Name	Item No.
TOLERANCE						Drawn	12.29.11	<b>AK-SATA-PC-015</b>
X.X	±0.40					Approved	Chappell	
X.XX	±0.25							Title
X.XXX	±0.15							Serial ATA Power Supply Cable 15-pin SATA Female <=> 4-pin ATX Female
Angle	±3°							Drawing No.
								rev00
								Replace
								Sheet
			Modification	Date	Name			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [assmann](#) manufacturer:*

Other Similar products are found below :

[AU-Y1007-R](#) [AK-320200-100-S](#) [AK-340305-010-W](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#)  
[AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK-340301-030-S](#) [AK-340305-020-W](#)  
[AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [DN-91524U](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#)  
[DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AT-K-26-10-W/1000](#)  
[AWG28-15/G/300](#) [ATUP-P305T](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-](#)  
[16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-330105-300-S](#) [AK-340406-001-W](#) [A-MCSSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-](#)  
[9/G/300](#) [V25HK](#) [A-LED8-1WAAS-MR7-1](#) [AWP2 16-7240](#)