

1	2	3	4	5	6	7																																	
A	B	C	D	E	F	G																																	
<p>PIN OUT</p> <table border="1"> <thead> <tr> <th>CN1</th> <th>WIRE COLOR</th> <th>CN2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>WHITE</td> <td>1</td> </tr> <tr> <td>2</td> <td>ORANGE</td> <td>2</td> </tr> <tr> <td>3</td> <td>WHITE</td> <td>3</td> </tr> <tr> <td>6</td> <td>GREEN</td> <td>6</td> </tr> <tr> <td>4</td> <td>BLUE</td> <td>4</td> </tr> <tr> <td>5</td> <td>WHITE</td> <td>5</td> </tr> <tr> <td>7</td> <td>WHITE</td> <td>7</td> </tr> <tr> <td>8</td> <td>BROWN</td> <td>8</td> </tr> <tr> <td>SHELL</td> <td>BRAID</td> <td>SHELL</td> </tr> </tbody> </table>							CN1	WIRE COLOR	CN2	1	WHITE	1	2	ORANGE	2	3	WHITE	3	6	GREEN	6	4	BLUE	4	5	WHITE	5	7	WHITE	7	8	BROWN	8	SHELL	BRAID	SHELL			
CN1	WIRE COLOR	CN2																																					
1	WHITE	1																																					
2	ORANGE	2																																					
3	WHITE	3																																					
6	GREEN	6																																					
4	BLUE	4																																					
5	WHITE	5																																					
7	WHITE	7																																					
8	BROWN	8																																					
SHELL	BRAID	SHELL																																					
<p>② Tolerance</p> <table border="1"> <thead> <tr> <th>Length(meter)</th> <th>Max-Δl</th> <th>Min-Δl</th> </tr> </thead> <tbody> <tr> <td>0.5</td> <td>+0.03</td> <td>-0.025</td> </tr> <tr> <td>1</td> <td>+0.04</td> <td>-0.035</td> </tr> <tr> <td>2</td> <td>+0.06</td> <td>-0.06</td> </tr> <tr> <td>3</td> <td>+0.09</td> <td>-0.09</td> </tr> <tr> <td>5</td> <td>+0.15</td> <td>-0.15</td> </tr> <tr> <td>7</td> <td>+0.21</td> <td>-0.21</td> </tr> <tr> <td>10</td> <td>+0.3</td> <td>-0.3</td> </tr> <tr> <td>15</td> <td>+0.45</td> <td>-0.45</td> </tr> <tr> <td>20</td> <td>+0.6</td> <td>-0.6</td> </tr> <tr> <td>30</td> <td>+0.9</td> <td>-0.9</td> </tr> </tbody> </table>							Length(meter)	Max-Δl	Min-Δl	0.5	+0.03	-0.025	1	+0.04	-0.035	2	+0.06	-0.06	3	+0.09	-0.09	5	+0.15	-0.15	7	+0.21	-0.21	10	+0.3	-0.3	15	+0.45	-0.45	20	+0.6	-0.6	30	+0.9	-0.9
Length(meter)	Max-Δl	Min-Δl																																					
0.5	+0.03	-0.025																																					
1	+0.04	-0.035																																					
2	+0.06	-0.06																																					
3	+0.09	-0.09																																					
5	+0.15	-0.15																																					
7	+0.21	-0.21																																					
10	+0.3	-0.3																																					
15	+0.45	-0.45																																					
20	+0.6	-0.6																																					
30	+0.9	-0.9																																					
<p>① Order code: A-MC^{SS}P60XXX : color Grey</p> <p>order lengths in meter: 0.5, 1, 2, 3, 5, 7, 10, 15, 20, 30</p> <p>① Order code: A-MC^{SS}P60XXX/X</p> <p>order lengths in meter: 0.5, 1, 2, 3, 5, 7, 10, 15, 20, 30</p> <p>order color: (R)Red, (Y)Yellow, (G)Green, (B)Blue</p> <p>Electrical test: Open/Short/Intermittence: 100%</p>																																							
<table border="1"> <thead> <tr> <th>NO.</th> <th>NAME.</th> <th>QTTY</th> <th>DATE</th> <th>NAME</th> </tr> </thead> <tbody> <tr> <td>③</td> <td>Molding PVC</td> <td>2</td> <td></td> <td></td> </tr> <tr> <td>②</td> <td>RJ45 CONN</td> <td>2</td> <td></td> <td></td> </tr> <tr> <td>①</td> <td>CABLE</td> <td>1</td> <td></td> <td></td> </tr> </tbody> </table>							NO.	NAME.	QTTY	DATE	NAME	③	Molding PVC	2			②	RJ45 CONN	2			①	CABLE	1															
NO.	NAME.	QTTY	DATE	NAME																																			
③	Molding PVC	2																																					
②	RJ45 CONN	2																																					
①	CABLE	1																																					
<p>Customer-No.</p> <p>ASSMANN WSW-No. A-MC^{SS}P60XXX/X</p> <p>Drawing-No. ASS 7542 CA</p> <p>Replace</p>																																							
<p>Scale FREE</p> <p>TOLERANCE</p> <p>DIM TOL</p> <p>Angle TOL</p>																																							
<p>② Clarify the tolerance</p> <p>23.08.2018 Segal</p>																																							
<p>① Add Grey color order code</p> <p>11.08.2016 Ray</p>																																							
<p>① Drawn</p> <p>01.02.2016 Joanna</p>																																							
<p>Modification</p> <p>Id.</p>																																							
<p>Date</p> <p>01.02.2016 Joanna</p>																																							
<p>Name</p> <p>Joanna</p>																																							
<p>DATE</p> <p>01.02.2016</p>																																							
<p>NAME</p> <p>Joanna</p>																																							
<p>DATE</p> <p>23.08.2018</p>																																							
<p>NAME</p> <p>Amy</p>																																							
<p>DATE</p> <p>01.02.2016</p>																																							
<p>NAME</p> <p>Joanna</p>																																							

ROHS compliant
Unit: mm



ASS 7542 CA rev02

Sheet

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [AK-320200-100-S](#) [AK-330114-050-S](#) [AK-340100-020-S](#) [AK-340305-010-W](#) [AK-340305-030-W](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#) [AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK-320200-030-S](#) [AK-340100-030-S](#) [AK-340301-020-S](#) [AK-340301-030-S](#) [AK-340305-020-W](#) [AK-340602-000-S](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [A-LED8-1WAAS-MR7-1](#) [AT-S-26-8/8/W-7/R](#) [DN-91524U](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AK-300136-018-S](#) [AT-K-26-10-W/1000](#) [AWG28-15/G/300](#) [ATUP-P305T](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#) [AWG28-9/F/300](#)