



Specifications:

Material:
 Housing: Poly Carbonate(PC) UL94V-2
 Contact: Phosphor Bronze with 2 prongs
 Plating: 6u" gold plated
 100u" Nickel under plated
 Operating temperature: -40°C to +125°C

Electrical:
 Current rating: 250V AC max. at 2A
 Dielectric: 500V AC
 Insulation resistance: 500MΩ
 Termination resistance: 35mΩ max after environmental tests
 Tensile strength: 20 LBS (89N) min.
 Durability: 500 mating cycles

Complies with FCC68/F
 ② Wire gauge: 30AWG-24AWG Stranded wire
 Cable OD size: flat cable 2.5x5.0±0.02mm
 Wire size: 0.95±0.05mm

RoHS compliant
 Unit: mm

Scale	Free						Date	Name	Customer-No.	
TOLERANCE						Drawn	26.05.2014	Ray		
X.X	±0.20					Approved	03.04.2019	Amy	ASSMANN WSW-No.	
X.XX	±0.10								A-MO 4/4-SF	
X.XXX	±0.05	②	Add cable wire size information	03.04.2019	Amy				Drawing-No.	
DIM	TOL	①	Update the dimensions	03.05.2016	Amy	ASSMANN WSW components			ASS 6448 CO	rev02
Angle	±2°	③	Drawn	26.05.2014	Ray		Replace	Sheet		
Angle	TOL	Id.	Modification	Date	Name					

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [A-DF15-HOOD-WP](#) [A-USB-1](#) [AK-320200-100-S](#) [AK-330109-020-S](#) [AK-330114-050-S](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#) [AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK-320108-030-S](#) [AK-320200-030-S](#) [AK-330107-010-S](#) [AK-330107-020-S](#) [AK-330505-000-S](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [AWH-24G-E202-IDC](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [AK500/14-OE-5-2](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AK-320100-020-S](#) [AK-320400-002-S](#) [AT-K-26-6-B/500](#) [AK-400102-008-R](#) [AT-K-26-6-W/100](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK-340102-010-W](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#)