



TERMINATION:

P1	COLOR
1	BLACK
2	RED
3	GREEN
4	YELLOW

Extended length is with 500g of force

Materials:

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36"[.014MM] Thick Phosphor Bronze
- Connector: 50µ" of Selective Gold Contact Plating
 - Area, Gold flash over the remainder
 - Over 2.54µm[.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X4C): PP6331 ID 0.95-1.0
- Jacket: PVC NOUL 80P
- Package: Individual PE Bag

Extended Length ("L2")	Typical Retracted Length ("L1")
120.0 Inches - 138.0 Inches	25 Inches
3,048.0MM-3,505.2MM	635.0MM

ITEM NO

AT-C-26-4/4/B-10-OE

TITLE NON-UL 26AWG (0.16/7)*4C, O.D.: 2.4*4.8MM
Single Plug, 50µ" of contact plating, BLACK



1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED

Copyright 2009 by Assmann Electronic Components All International Rights Reserved



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for assmann manufacturer:

Other Similar products are found below:

AU-Y1007-R A-DF15-HOOD-WP A-USB-1 AK-320200-100-S AK-340603-000-S AK500-RA-6-0.5-R AK669/2-18-BLACK-R AT-K-26-10-B/1000 AU-Y1008-2-R AWG28-50/G/300 AWH26G-0232 AB-900 AB-970 AB-984 A-DS 15PP AK3730X-R AK579/F-2 A-MCU60010/Y A-PC2302-030028-1 AT-S-26-8/8/W-7/R AWH-24G-E202-IDC DK-2631-05 DN-91624U DN-91548U DK-1511-015/WH A-MCU60030/R AWH50G-0202-T-R AK500/16-OE-7-0.5 AK500/14-OE-5-2 DK-1611-020/B DK-1511-100/G AK-320400-002-S AT-K-26-6-B/500 AK-400102-008-R AT-K-26-6-W/100 AWP 10-7540-T AK-330118-100-S AK-330118-300-S AK-340102-010-W AK500/U-1-R AK-SATA-030DL-R AWG28-16/G/300 AWG28-9/F/300 ADIP16-G-LC-R AK-310203-018-E AK-330105-300-S AK-340406-001-W A-MCSSP60020/B-R A-MO-8/8-F50-R AWG28-20/G/300