



NOTES:

MATERIAL

⑥ 1. Insulator Material: PA9T+30%GF (UL94V-0), Black

2. Contact Material : Brass

3. Contact Plating : Gold flash Over 50µ"Ni

ELECTRICAL

1. Current Rating : 1.5AMP

2. Withstand Voltage : 500V AC/DC

3. Contact Resistance : 20mΩ max

4. Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

1. Operation Temperature: -40°C to +105°C

2. Packing: Tube

④ xx: 06, 10, 14, 16, 20, 24, 26, 30, 34, 40, 44, 50, 60

RoHS compliant
Unit: mm
 File No.: E198287 ③

Scale	Free	⑥	Add the soldering profile & Change the material to PA9T		22.03.2016	Winnie
TOLERANCE		⑤	Update the packing		25.02.2014	Amy
X.X	±0,40	④	Add 06 poles version into the drawing		08.02.2014	Amy
X.XX	±0,25	③	Add UL-File No		12.12.2013	Winnie
X.XXX	±0,15	②	Update		29.06.2009	Dean
Angle°	±3°	①	Drawn		25.01.2006	Alex
			Id.			Name

ASSMANN
WSW/ components

Customer-No.	Date	Name
	25.01.2006	Alex
	22.03.2016	Winnie

Customer-No.	ASSMANN WSW-No.	Drawing-No.
	AWHW2 XXA-0202	

Replace	ASS 2318 CO	rev06

1	2	3	4	5	6	7
A	B	C	D	E	F	G
H						

1

2

3

4

5

6

7

A

SMT Type Product Past IR Reflow Graph



A

B

B

C

C

D

D

E

E

F

F

RoHS compliant
Unit: mm



Scale	Free
TOLERANCE	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle°	±3°

⑥	Add the soldering profile & Change the material to PA9T	22.03.2016	Winnie
⑤	Update the packing	25.02.2014	Amy
④	Add 06 poles version into the drawing	08.02.2014	Amy
③	Add UL-File No	12.12.2013	Winnie
②	Update	29.06.2009	Dean
①	Drawn	25.01.2006	Alex

⑥	Add the soldering profile & Change the material to PA9T	22.03.2016	Winnie
⑤	Update the packing	25.02.2014	Amy
④	Add 06 poles version into the drawing	08.02.2014	Amy
③	Add UL-File No	12.12.2013	Winnie
②	Update	29.06.2009	Dean
①	Drawn	25.01.2006	Alex

⑥	Add the soldering profile & Change the material to PA9T	22.03.2016	Winnie
⑤	Update the packing	25.02.2014	Amy
④	Add 06 poles version into the drawing	08.02.2014	Amy
③	Add UL-File No	12.12.2013	Winnie
②	Update	29.06.2009	Dean
①	Drawn	25.01.2006	Alex

⑥	Add the soldering profile & Change the material to PA9T	22.03.2016	Winnie
⑤	Update the packing	25.02.2014	Amy
④	Add 06 poles version into the drawing	08.02.2014	Amy
③	Add UL-File No	12.12.2013	Winnie
②	Update	29.06.2009	Dean
①	Drawn	25.01.2006	Alex

Customer-No.	ASSMANN WSW-No.	AWHW2 XXA-0202
Drawing-No.	ASS 2318 CO	rev06
Replace		Sheet 2/2

ASSMANN
WSW/ components

1

2

3

4

5

6

7

SV3505

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [AK-320200-100-S](#) [AK-340305-010-W](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#)
[AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK-340301-030-S](#) [AK-340305-020-W](#)
[AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [DN-91524U](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#)
[DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AT-K-26-10-W/1000](#)
[AWG28-15/G/300](#) [ATUP-P305T](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-](#)
[16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-330105-300-S](#) [AK-340406-001-W](#) [A-MCSSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-](#)
[9/G/300](#) [V25HK](#) [A-LED8-1WAAS-MR7-1](#) [AWP2 16-7240](#)