



RECOMMENDED P.C.B BOARD
HOLE LAYOUT
TOLERANCES: ±0.05mm

Pin No.	A	B	C
10	20.32	10.16	18.02
14	25.40	15.24	23.10
16	27.94	17.78	25.64
20	33.02	22.86	30.72
24	38.10	27.94	35.80
26	40.64	30.48	38.34
30	45.72	35.56	43.42
34	50.80	40.64	48.50
40	58.42	48.26	56.12
50	71.12	60.96	68.82
60	83.82	73.66	81.52
64	88.90	78.74	86.60

Material:

- Insulator: Polyester (UL94V-0)
- Insulator Standard: PBT
- Contact: Brass
- Contact Plating: Tin, Gold Flash or 30µ" Gold (Selective)

Electrical:

- Current Rating: 3A
- Contact Resistance: 20mΩ Max.
- Insulation Resistance: 5,000MΩ Min.
- Withstanding Voltage: AC 1,000V
- Operation Temperature: -40°C to +105°C

Order Code: AWHWxxG-0x02-T-R

Order pin number: 10,14,16,
20,24,26,30,34,40,50,60,64

Contact plating: 30µ" Gold (1),
Gold Flash (2), Tin (5)

Unit: mm



Scale	as shown				Date	Name	Title
TOLERANCE					Drawn	Wilson	Boxheader - Low Profile 10-64 pin, straight pin, 2.54mm pitch
X.	±0.50				Approved	Groll	ASSMANN WSW-No.
X.X	±0.35						AWHWxxG-0x02-T-R
X.XX	±0.25						Drawing-No.
DIM	TOL						rev01
X.°	±1°						
X.X°	±0.5°	①	Updated all information	13.03.13	Wilson		
Angle	TOL	Id.	Modification	Date	Name		Sheet 1/1



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [assmann](#) manufacturer:

Other Similar products are found below :

[AU-Y1007-R](#) [A-DF15-HOOD-WP](#) [A-USB-1](#) [AK-320200-100-S](#) [AK-340603-000-S](#) [AK500-RA-6-0.5-R](#) [AK669/2-18-BLACK-R](#) [AT-K-26-10-B/1000](#) [AU-Y1008-2-R](#) [AWG28-50/G/300](#) [AWH26G-0232](#) [AB-900](#) [AB-970](#) [AB-984](#) [A-DS 15PP](#) [AK3730X-R](#) [AK579/F-2](#) [A-MCU60010/Y](#) [A-PC2302-030028-1](#) [AT-S-26-8/8/W-7/R](#) [AWH-24G-E202-IDC](#) [DK-2631-05](#) [DN-91624U](#) [DN-91548U](#) [DK-1511-015/WH](#) [A-MCU60030/R](#) [AWH50G-0202-T-R](#) [AK500/16-OE-7-0.5](#) [AK500/14-OE-5-2](#) [DK-1611-020/B](#) [DK-1511-100/G](#) [AK-320400-002-S](#) [AT-K-26-6-B/500](#) [AK-400102-008-R](#) [AT-K-26-6-W/100](#) [AWP 10-7540-T](#) [AK-330118-100-S](#) [AK-330118-300-S](#) [AK-340102-010-W](#) [AK500/U-1-R](#) [AK-SATA-030DL-R](#) [AWG28-16/G/300](#) [AWG28-9/F/300](#) [ADIP16-G-LC-R](#) [AK-310203-018-E](#) [AK-330105-300-S](#) [AK-340406-001-W](#) [A-MCSSP60020/B-R](#) [A-MO-8/8-F50-R](#) [AWG28-9/G/300](#)