	1	1 2		3		4		5			6			7		
А		—A →B	4	i				DIMENSION POSITION A B POSITION A B					251.0	A		
В					0.15 🕲				12P 14P	19.80 22.34	10.16 12.70 15.24	30P 34P 36P	35.04 27. 37.58 30.4 42.66 35. 47.74 40. 50.43 43.	48 56 64 18	В	
С				7.00±0.15					27.42	B B B C B C C C C C C C C C C C C C C C	44P	55.36 48. 60.64 53 68.06 60.	.34	С		
D			10.50±0.15 -	64P 85.82 81.62 MATERIALS:									D			
E	ງ ໂ							INSULATOR:P.B.T.30%GLASS FIBER,UL94V-0 CONTACT MATERIAL:BRASS OR PHOSPHOR BRONZE, UNDERPLATE: NICKEL CONTACT AREA: 100u" TIN/LEAD FREE(MATTE TIN) E ELECTRICAL: CURRENT RATING:1AMP. INSULATION RESISTANCE:1000MΩ MIN.								
F	Ę				DIELECTRIC WITHSTANDING:500VAC OPERATING TEMPERATURE:-55°C~+105°C								F			
G		Scale TOLERA X.X X.XX	±0.40 ±0.25	CE 0.40 0.25				Drawn Approved	10.19.		Name happell	AWPXX-8540 Title IDC-So	D-T-R Witho cket, Pitch 2	R With Strain Relief R Without Strain Relief , Pitch 2.54X2.54mm, Lug, Tin Plated		
н	Ro Comp	HS plaint	±0.15 ±3°	Modifica	tion	Date	Name		ASSMAN			Drawing No.		rev00	Н	
	1	2		3		4		5				6		7		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for assmann manufacturer:

Other Similar products are found below :

AU-Y1007-R A-DF15-HOOD-WP A-USB-1 AK-320200-100-S AK-340603-000-S AK500-RA-6-0.5-R AK669/2-18-BLACK-R AT-K-26-10-B/1000 AU-Y1008-2-R AWG28-50/G/300 AWH26G-0232 AB-900 AB-970 AB-984 A-DS 15PP AK3730X-R AK579/F-2 A-MCU60010/Y A-PC2302-030028-1 AT-S-26-8/8/W-7/R AWH-24G-E202-IDC DK-2631-05 DN-91624U DN-91548U DK-1511-015/WH A-MCU60030/R AWH50G-0202-T-R AK500/16-OE-7-0.5 AK500/14-OE-5-2 DK-1611-020/B DK-1511-100/G AK-320400-002-S AT-K-26-6-B/500 AK-400102-008-R AT-K-26-6-W/100 AWP 10-7540-T AK-330118-100-S AK-330118-300-S AK-340102-010-W AK500/U-1-R AK-SATA-030DL-R AWG28-16/G/300 AWG28-9/F/300 ADIP16-G-LC-R AK-310203-018-E AK-330105-300-S AK-340406-001-W A-MCSSP60020/B-R A-MO-8/8-F50-R AWG28-9/G/300