| | 1 | 2 | 3 | 4 | | 5 | | 6 | 7 | | |
|---|---|-------------------|-------------------------|----------|---------|---|---|-------------------------|---|------------|---|
| A | | | | | | | | | | A | |
| В | 17 17 17 | A | | 5.95 | | 06P 12.1 08P 14.7 10P 17.2 12P 19.8 | 8 05.08 2 07.62 6 10.16 | 24P 3 26P 3 30P 4 | 5.04 27.94 7.58 30.48 2.66 35.56 7.74 40.64 | | В |
| С | | | | 5.95 K | | 14P 22.3 16P 24.8 18P 27.4 | 34 15.24 38 17.78 42 20.32 36 22.86 | 36P 5 40P 5 44P 6 | 0.43 43.18 5.36 48.26 0.64 53.34 8.06 60.96 | | С |
| D | | | ł | 6.95 | | POSITION A 60P 80.74 64P 85.82 | B 76.54 81.62 | | | | D |
| E | 2:54 | B 2.54 3.60 | 56.5 | | | MATERIALS: INSULATOR:P.B.T.30%GLASS FIBER,UL94V-0 CONTACT MATERIAL:BRASS OR PHOSPHOR BRONZE, UNDERPLATE: NICKEL CONTACT AREA: 100u" TIN/LEAD FREE(MATTE TIN) ELECTRICAL: | | | | | |
| F | CURRENT RATING:1AMP. INSULATION RESISTANCE:1000MΩ MIN. DIELECTRIC WITHSTANDING:500VAC OPERATING TEMPERATURE:-55°C~+105°C | | | | | | | | | | F |
| G | | X.XX ± | £0.40 £0.25 | | | Drawn 10.19.11 Approved | Name Chappell | AWPxx-7540 | -T-R With Strain -T-R Without Str et, Pitch 2.54X2 .ug, Tin Plated | ain Relief | G |
| Н | Ro Com | http://www.second | ±0.15 ±3° Modific | ation Da | te Name | | | Drawing No. | | ev00 | Н |
| | 1 | 2 | 3 | 4 | | 5 | | 6 | 7 | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for assmann manufacturer:

Other Similar products are found below :

AU-Y1007-R A-DF15-HOOD-WP A-USB-1 AK-320200-100-S AK-340603-000-S AK500-RA-6-0.5-R AK669/2-18-BLACK-R AT-K-26-10-B/1000 AU-Y1008-2-R AWG28-50/G/300 AWH26G-0232 AB-900 AB-970 AB-984 A-DS 15PP AK3730X-R AK579/F-2 A-MCU60010/Y A-PC2302-030028-1 AT-S-26-8/8/W-7/R AWH-24G-E202-IDC DK-2631-05 DN-91624U DN-91548U DK-1511-015/WH A-MCU60030/R AWH50G-0202-T-R AK500/16-OE-7-0.5 AK500/14-OE-5-2 DK-1611-020/B DK-1511-100/G AK-320400-002-S AT-K-26-6-B/500 AK-400102-008-R AT-K-26-6-W/100 AWP 10-7540-T AK-330118-100-S AK-330118-300-S AK-340102-010-W AK500/U-1-R AK-SATA-030DL-R AWG28-16/G/300 AWG28-9/F/300 ADIP16-G-LC-R AK-310203-018-E AK-330105-300-S AK-340406-001-W A-MCSSP60020/B-R A-MO-8/8-F50-R AWG28-9/G/300