	1	2	3	4	Ę	ō		6	7	
A	Material: 1 RJ45 Jack Housing: ABS, UL94V-0 - with optional color								A	
В	2. Jack Bracket Set: PBT, UL94V-0 3. RJ45 Jack Contact Material & Finish						I & Finished i0 Micro-inch Gc	Gold		
С	 PIN.8 PIN.1 30.3±0.2 4. IDC Housing: PC, 94V-2 5. IDC Terminal material & finished: Phosphor Bronze w/Min. 50 Micro-inch Tin plated Suitable for 23-24AWG stranded & solid wire 6. IDC CAP: PC, UL94V-2 								С	
D					InsertionRetention	T568A & T5	0 GM for : 7.7Kg b	etween Jack & F	Plug	D
E	CATR				 Durabil unm minu cycle 	lity: Jack: 75 ating test, In ite max. Con es.	0 cycles sertion cy ntact resis	Plug-Jack matin /cles at 20 cycle stance test per 1 formance is in c	s/ 00	E
F	with the ANSI/TIA/EIA 568 B.2-1 standard Unit: MM±0.1MM									F
	DICIT	Scale	1:1				Name	Item No.		
G	DIGIT	US TOLERANG	CE 0.40		Drawn	12.20.11	Chappell	DN-93	601-U/BI	G
		X.XX ±	0.25		Approved				ielded Keystone Jack - ree Type, Black	
н	Ro		±3°			SMA		Drawing No.	rev0	0 н
			Modifica	ation Date N		\\%\ \$ \\// compon		Replace Sheet		
	1	2	3	4	Ę	5		6	7	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for assmann manufacturer:

Other Similar products are found below :

AU-Y1007-R A-DF15-HOOD-WP A-USB-1 AK-320200-100-S AK-340603-000-S AK500-RA-6-0.5-R AK669/2-18-BLACK-R AT-K-26-10-B/1000 AU-Y1008-2-R AWG28-50/G/300 AWH26G-0232 AB-900 AB-970 AB-984 A-DS 15PP AK3730X-R AK579/F-2 A-MCU60010/Y A-PC2302-030028-1 AT-S-26-8/8/W-7/R AWH-24G-E202-IDC DK-2631-05 DN-91624U DN-91548U DK-1511-015/WH A-MCU60030/R AWH50G-0202-T-R AK500/16-OE-7-0.5 AK500/14-OE-5-2 DK-1611-020/B DK-1511-100/G AK-320400-002-S AT-K-26-6-B/500 AK-400102-008-R AT-K-26-6-W/100 AWP 10-7540-T AK-330118-100-S AK-330118-300-S AK-340102-010-W AK500/U-1-R AK-SATA-030DL-R AWG28-16/G/300 AWG28-9/F/300 ADIP16-G-LC-R AK-310203-018-E AK-330105-300-S AK-340406-001-W A-MCSSP60020/B-R A-MO-8/8-F50-R AWG28-9/G/300