

## Standard Microchip



The world's smallest surface mount Tantalum capacitor, small enough to create space providing room for ideas to grow.

TACmicrochip™ is a major breakthrough in miniaturization without reduction in performance.

It offers you the highest energy store in a small case size down to 0402; enhanced high frequency operation through unique ESR performance with temperature and voltage stability is also offered.




LEAD-FREE



HALOGEN-FREE COMPOUNDS

ENVIRONMENTAL FRIENDLY COMPONENT



### CASE DIMENSIONS: millimeters (inches)

Code	EIA Code	EIA Metric	Length (L)	Width (W)	Height (H)	Termination Spacing(S)	Minimum Termination Length (Lt)	Average Mass
K	0402	1005-07	1.00 <sup>+0.20</sup> <sub>-0.00</sub> (0.039 <sup>+0.008</sup> <sub>-0.000</sub> )	0.50 <sup>+0.20</sup> <sub>-0.00</sub> (0.020 <sup>+0.008</sup> <sub>-0.000</sub> )	0.50 <sup>+0.20</sup> <sub>-0.00</sub> (0.020 <sup>+0.008</sup> <sub>-0.000</sub> )	0.40 min.	0.10 (0.004)	2.0mg
L	0603	1608-10	1.60 <sup>+0.20</sup> <sub>-0.00</sub> (0.063 <sup>+0.008</sup> <sub>-0.000</sub> )	0.85 <sup>+0.15</sup> <sub>-0.00</sub> (0.033 <sup>+0.006</sup> <sub>-0.000</sub> )	0.85 <sup>+0.15</sup> <sub>-0.00</sub> (0.033 <sup>+0.006</sup> <sub>-0.000</sub> )	0.55 min.	0.15 (0.006)	8.6mg
R	0805	2012-15	2.00 <sup>+0.20</sup> <sub>-0.00</sub> (0.079 <sup>+0.008</sup> <sub>-0.000</sub> )	1.35 <sup>+0.15</sup> <sub>-0.00</sub> (0.053 <sup>+0.006</sup> <sub>-0.000</sub> )	1.35 <sup>+0.15</sup> <sub>-0.00</sub> (0.053 <sup>+0.006</sup> <sub>-0.000</sub> )	0.70 min.	0.15 (0.006)	29.9mg
A	1206	3216-18	3.20±0.20 (0.126±0.008)	1.60±0.20 (0.063±0.008)	1.60±0.20 (0.063±0.008)	1.80 min.	0.15 (0.006)	44.6mg

### HOW TO ORDER

<b>TAC</b>	<b>L</b>	<b>226</b>	<b>M</b>	<b>004</b>	<b>R</b>	<b>TA</b>
Type TACmicrochip™	Case Size 0402=K 0603=L 0805=R 1206=A	Capacitance Code pF code: 1st two digits represent significant figures, 3rd digit represents multiplier (number of zeros to follow)	Tolerance K=±10% M=±20%	Rated DC Voltage 002=2Vdc 003=3Vdc 004=4Vdc 005=5Vdc 006=6.3Vdc 010=10Vdc 016=16Vdc 020=20Vdc 025=25Vdc 035=35Vdc	Packaging (see table below)	Alternative characters may be used for special requirements

### Packaging Suffix

Reel Size	Standard Tin Termination Plastic Tape	Standard Tin Termination Paper Tape	Gold Termination Plastic Tape
Case	A/R/L	K	A/R/L
7"	RTA	PTA	ATA
4¼"	XTA	QTA	FTA

### TECHNICAL SPECIFICATIONS

Technical Data:	All technical data relate to an ambient temperature of +25°C
Capacitance Range:	0.47 µF to 150 µF
Capacitance Tolerance:	±10%; ±20%
Leakage Current DCL:	0.01CV or 0.5µA whichever is the greater
Rated Voltage (V <sub>R</sub> )	≧ +85°C: 2 3 4 5 6.3 10 16 20 25 35
Category Voltage (V <sub>C</sub> )	≧ +125°C: 1.3 2 2.7 3.3 4 7 10 13 17 23
Surge Voltage (V <sub>S</sub> )	≧ +85°C: 2.7 3.9 5.2 6.5 8 13 20 26 32 46
Surge Voltage (V <sub>S</sub> )	≧ +125°C: 1.7 2.6 3.2 4 5 8 12 16 20 28
Temperature Range:	-55°C to +125°C
Reliability:	1% per 1000 hours at 85°C, V <sub>R</sub> with 0.1Ω/V series impedance, 60% confidence level
Termination Finish:	Nickel and Tin Plating (standard), Nickel and Gold Plating option available upon request

### STANDARD COMMERCIAL RANGE (EIA Sizes) (LETTER DENOTES CASE SIZE)

Capacitance		Voltage Rating DC (V <sub>R</sub> ) at 85°C									
µF	Code	2.0V	3.0V	4.0V	5.0V	6.3V	10V	16V	20V	25V	35V
0.33	334										
0.47	474						K/L	L			
0.68	684						K/L	L			
1.0	105					K/L	K/L	L		R	
1.5	155			L		L	L	L			
2.2	225		K/L	L		K/L	L	L			
3.3	335	K/L	K/L	L		L	L/R				
4.7	475	K/L	K/L	L		L	L/R		R		
6.8	685	L	L	L		L/R	R				
10	106	K/L	L	L/R		L/R	L/R	R			
15	156		R	L/R		L/R	R				
22	226	R	L/R	L/R	L	R	R				
33	336	R	R	R		R	A				
47	476	L/R	R	R		A	A				
68	686	R	R	A							
100	107		R/A	A		A					
150	157	A									
220	227	A									

Developmental Ratings - subject to change

Standard Height Profile: K, L, R, A Case

Low Profile: N, U, H, T, V Case

Custom Low Profile: X Case

### RATINGS & PART NUMBER REFERENCE

AVX Part No.	EIA	Case Size	Capacitance (µF)	Rated Voltage (V)	DCL (µA) Max.	DF % Max.	ESR Max. (Ω) @100kHz
TACK335M002#	0402	K	3.3	2	0.5	8	15
TACL335*002#	0603	L	3.3	2	0.5	6	7.5
TACK475M002#	0402	K	4.7	2	0.5	12	15
TACL475*002#	0603	L	4.7	2	0.5	6	7.5
TACL685*002#	0603	L	6.8	2	0.5	6	7.5
TACK106M002#	0402	K	10	2	0.5	15	15
TACL106*002#	0603	L	10	2	0.5	10	7.5
TACR226*002#	0805	R	22	2	0.5	8	5
TACR336*002#	0805	R	33	2	0.7	10	5
TACR476*002#	0805	R	47	2	0.9	10	5
TACR686M002#	0805	R	68	2	1.4	14	5
TACA157M002#	1206	A	150	2	3.0	20	1
TACK225M003#	0402	K	2.2	3	0.5	6	15
TACL225*003#	0603	L	2.2	3	0.5	6	7.5
TACK335M003#	0402	K	3.3	2	0.5	8	15
TACL335*003#	0603	L	3.3	3	0.5	6	7.5
TACK475M003#	0402	K	4.7	3	0.5	12	15
TACL475*003#	0603	L	4.7	3	0.5	6	7.5
TACL685*003#	0603	L	6.8	3	0.5	6	7.5
TACL106*003#	0603	L	10	3	0.5	10	7.5
TACR156*003#	0805	R	15	3	0.5	8	5
TACL226M003#	0603	L	22	3	0.7	20	7.5
TACR226*003#	0805	R	22	3	0.7	8	5
TACR336*003#	0805	R	33	3	1.0	10	5
TACR476*003#	0805	R	47	3	1.5	10	5
TACR686M003#	0805	R	68	3	2.0	14	5
TACA107M003#	1206	A	100	3	3.0	15	1
TACL155*004#	0603	L	1.5	4	0.5	6	7.5
TACL225*004#	0603	L	2.2	4	0.5	6	7.5
TACL335*004#	0603	L	3.3	4	0.5	6	7.5
TACL475*004#	0603	L	4.7	4	0.5	6	7.5
TACL685*004#	0603	L	6.8	4	0.5	8	7.5
TACL106M004#	0603	L	10	4	0.5	10	7.5
TACR106*004#	0805	R	10	4	0.5	8	5
TACL156M004#	0603	L	15	4	0.6	20	7.5
TACR156*004#	0805	R	15	4	0.6	8	5
TACL226M004#	0603	L	22	4	0.9	20	7.5
TACR226*004#	0805	R	22	4	0.9	8	5
TACR336*004#	0805	R	33	4	1.3	10	5
TACR476M004#	0805	R	47	4	1.9	14	5
TACA686M004#	1206	A	68	4	2.7	15	1
TACA107M004#	1206	A	100	4	4.0	20	1
TACL226M005#	0603	L	22	5	1.1	20	7.5

AVX Part No.	EIA	Case Size	Capacitance (µF)	Rated Voltage (V)	DCL (µA) Max.	DF % Max.	ESR Max. (Ω) @100kHz
TACK105M006#	0402	K	1.0	6.3	0.5	6	15
TACL105*006#	0603	L	1.0	6.3	0.5	6	7.5
TACL155*006#	0603	L	1.5	6.3	0.5	6	7.5
TACK225M006#	0402	K	2.2	6.3	0.5	8	15
TACL225*006#	0603	L	2.2	6.3	0.5	6	7.5
TACL335*006#	0603	L	3.3	6.3	0.5	6	7.5
TACL475*006#	0603	L	4.7	6.3	0.5	8	7.5
TACL685*006#	0603	L	6.8	6.3	0.5	10	7.5
TACR685*006#	0805	R	6.8	6.3	0.5	8	5
TACL106M006#	0603	L	10	6.3	0.6	10	6
TACR106*006#	0805	R	10	6.3	0.6	8	5
TACL156M006#	0603	L	15	6.0	0.9	20	7.5
TACR156*006#	0805	R	15	6.3	0.9	8	5
TACR226*006#	0805	R	22	6.3	1.4	10	5
TACR336*006#	0805	R	33	6.3	2.1	12	5
TACA476M006#	1206	A	47	6.3	3.0	15	1
TACA107M006#	1206	A	100	6.3	6.3	20	1
TACK474M010#	0402	K	0.47	10	0.5	6	15
TACL474*010#	0603	L	0.47	10	0.5	6	7.5
TACK684M010#	0402	K	0.68	10	0.5	8	15
TACL684*010#	0603	L	0.68	10	0.5	6	7.5
TACK105M010#	0402	K	1.0	10	0.5	6	15
TACL105*010#	0603	L	1.0	10	0.5	6	7.5
TACL155*010#	0603	L	1.5	10	0.5	6	7.5
TACL225*010#	0603	L	2.2	10	0.5	6	7.5
TACL335*010#	0603	L	3.3	10	0.5	8	7.5
TACR335*010#	0805	R	3.3	10	0.5	8	5
TACL475M010#	0603	L	4.7	10	0.5	10	6
TACR475*010#	0805	R	4.7	10	0.5	8	6
TACR685*010#	0805	R	6.8	10	0.7	8	5
TACL106M010#	0603	L	10	10	1.0	20	7.5
TACR106*010#	0805	R	10	10	1.0	8	5
TACR156*010#	0805	R	15	10	1.5	10	5
TACR226M010#	0805	R	22	10	2.2	14	5
TACA336M010#	1206	A	33	10	3.3	12	1
TACL474*016#	0603	L	0.47	16	0.5	6	7.5
TACL684*016#	0603	L	0.68	16	0.5	6	7.5
TACL105*016#	0603	L	1.0	16	0.5	6	7.5
TACL225M016#	0603	L	2.2	16	0.5	10	7.5
TACR106*016#	0805	R	10	16	1.6	10	5
TACR475M020#	0805	R	4.7	20	0.9	8	5
TACR105*025#	0805	R	1.0	25	0.5	8	5

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

\* Insert K for ±10% and M for ±20% Capacitance Tolerance

# Refer to packaging suffix for options

**NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Tantalum Capacitors - Polymer SMD category](#):*

*Click to view products by [AVX manufacturer](#):*

Other Similar products are found below :

[2R5TAE680ML](#) [T58BB226M025C0150](#) [23484-337](#) [TCJD227M010R0050E](#) [TCJC106M035R0200E](#) [TCJP105M025R0500E](#)  
[TCJD477M004R0040E](#) [TCNX476M035R0150](#) [ASG-P-V-A-1.000GHZ](#) [F381A336MSALZT](#) [FA1E566M10126VR](#) [NTP687M4TRD\(12\)F](#)  
[T520X477M006AHE040](#) [T541X336M050BH6710](#) [T541X337M016BH6720](#) [TCNT476M016R0200A](#) [ETCF680ML](#) [4TCE470ML](#)  
[4TCE470MIL](#) [4TCE330M](#) [6TCE100M](#) [6TCE150MI](#) [6TCE680M](#) [6TCE220M](#) [10TCE220ML](#) [4TCE220M](#) [4TAE470ML](#)  
[T520Y687M004ATE010](#) [T55V337M6R3C0050](#) [T55V337M004C0025](#) [T55V227M6R3C0050](#) [T55V227M004C0045](#) [T55V157M6R3C0035](#)  
[T55V157M010C0045](#) [T55D337M004C0050](#) [T55D107M010C0018](#) [T59EE337M016C0025](#) [T55V337M2R5C0025](#) [T55V337M004C0045](#)  
[T55V227M6R3C0040](#) [T55V227M004C0035](#) [T55V157M6R3C0045](#) [TCJD106M050R0090](#) [T55V157M004C0025](#) [T55D477M004C0040](#)  
[T55D337M6R3C0045](#) [T55D337M010C0040](#) [T55D227M6R3C0055](#) [T55D227M6R3C0050](#) [T55D227M6R3C0025](#)