

eBOX532-100-FL

Fanless Embedded System with AMD G-Series APU T40R 1.0 GHz

Features

- AMD G-Series APU T40R 1.0 GHz onboard
- AMD A50M FCH
- Ultra slim and compact design
- 4 USB 2.0 ports and 2 COM ports
- 1 GbE LAN port
- One 2.5" SATA HDD drive bay, 1 CompactFlash™
- VGA or DisplayPort



Specifications


Standard Color	Silver-Black
Construction	Aluminum extrusion and heavy-duty steel, IP40
CPU	AMD G-Series APU T40R 1.0 GHz onboard
System Memory	1 x 204-pin DDR3 SO-DIMM, up to 4GB
Chipset	AMD A50M FCH
BIOS	AMI
System I/O Outlet	2 x RS-232 (COM 1/2) 1 x VGA or 1 x DisplayPort 1 x Audio (Mic-in/Line-out) 1 x PS/2 keyboard/mouse 1 x 10/100/1000Mbps Ethernet (Realtek RTL8111E) 4 x USB 2.0 1 x VDC 5V power input
Watchdog Timer	255 levels, 1 ~ 255 sec.
Storage	1 x 2.5" SATA HDD drive bay 1 x CompactFlash™ slot
Expansion Interface	N/A
System Indicator	1 x green LED for system power-on 1 x orange LED for HDD active
Power Supply	Input: AC 100 ~ 240V, AC 40W adapter with lock Output: DC 5V @ 8A
Operating Temperature	0°C ~ +45°C (32°F ~ 113°F) (with W.T. HDD) 0°C ~ +50°C (32°F ~ 122°F) (with W.T. SSD & W.T. CF)
Humidity	10% ~ 90%, non-condensing
Dimensions	132 mm (5.19") (W) x 95.4 mm (3.75") (D) x 47.5 mm (1.87") (H)
Weight (net/gross)	0.5 kg (1.1 lb)/ 0.6 kg (1.32 lb)
Certificate	CE
EOS Support	XPE, Linux, WES, WES7

Packing List

- 1 x Quick manual
- 1 x Driver CD
- 1 x Y cable for PS/2 keyboard/mouse
- 1 x Screw pack
- 4 x Foot pad
- 1 x Power adapter
- 1 x Wall mount kit
- 1 x Power cord
- 1 x HDD mylar



▲ Front view



▲ Rear view

Power Protection

AC Version

- OVP (over voltage protection)
- SCP (short circuit protection)
- OPP (over power protection)

Ordering Information

Standard


eBOX532-100-FL1.0G-VGA	Fanless embedded system with AMD G-Series APU T40R 1.0 GHz, 1 GbE LAN, 4 USB, 2 COM, 40W AC/DC adapter and VGA
eBOX532-100-FL1.0G-PGA	Fanless embedded system with AMD G-Series APU T40R 1.0 GHz, 1 GbE LAN, 4 USB, 2 COM, 40W AC/DC adapter and DisplayPort

Optional

2.5" SATA HDD	40GB or above
2.5" SATA SSD	4GB or above
DDR3 SO-DIMM	512MB - 4GB
CompactFlash™	1GB or above
DIN-rail kit	881605300A0E
VESA mount kit	881605301A0E
Power cord	

*Specifications and certifications are based on options and may vary.

Dimensions



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Embedded Box Computers](#) category:

Click to view products by [Axiomtek](#) manufacturer:

Other Similar products are found below :

[tBOX312-870-FL-i7-DC](#) [tBOX313-835-FL-RJ-DC](#) [UPOS-3150-R0W0E](#) [ARK-20-S8A1E](#) [R2224WTTYSR](#) [BXNUC9i5QNX](#)
[BXNUC9i5QNX1](#) [BKNUC9V7QNX](#) [BKNUC9V7QNX1](#) [2-A0DF-2001](#) [BKCMB1ABB](#) [BKCMB1ABA](#) [EM3000-3845-8-128-WL-U-1](#)
[TANK-870AI-i5/8G/2A-R10](#) [PRFE21000038](#) [EM5000-I3-8-128-WL-W7-1](#) [EM3000-3845-8-128-WL-W7-1](#) [PRFE21000039](#) [AMOS-825-](#)
[1Q10A1](#) [UPS-EDAI-X70864-U01-DC01](#) [UPX-EDGEI7-A10-1664-F01](#) [MXE-211/M8G](#) [PXIe-3985/M16G](#) [PXIe-3987/M16G/SSD](#) [AIMB-](#)
[T1215DA-00Y0E](#) [AIMB-T1217DW-00Y0E](#) [AIMB-T12315A-00Y0E](#) [AMAX-5580-54000A](#) [APAX-5580-474AE](#) [ARK-6322-Q0A2E](#) [DS-](#)
[100GF-S8A1E](#) [DS-100GL-S8A1E](#) [EPC-R4680CQ-XAA1E](#) [ESRP-CSS-UNO2484](#) [ITA-1611-10A1E](#) [ITA-1711-10A1E](#) [MIC-710AI-00A1](#)
[MIC-720AI-00A1](#) [UNO-247-J1N1AE](#) [UTX-3115FS-S6A2E](#) [AMI220AF-4L-7500](#) [ELIT-1200](#) [AIE100-903-FL](#) [EBOX671-517-FL-DC](#)
[MVS900-511-FL](#) [AMS200](#) [SE-92-I7](#) [SI-606](#) [SI-60E](#) [TANK-760-HM86i-i5/4G-R10](#)