




4411

Cobalt HSS-E Drill Bits for Metal

PRODUCT DETAILS

- Size 1 mm up to 4 mm, two drills in each tube
- Top angle of 135° with self-centring split-point tip for quick cutting and perfect centring
- Speed Point, no need to pre-punch or pilot drill up to 10mm diameter
- Drill bits have a cylindrical shank and designed for use in drill stands and drill drivers
- The cobalt high-speed steel (HSS) provides long lasting high performance when drilling in stainless steel materials
- Cobalt drills work good in following materials alloyed/non-alloyed steel, stainless steel, cast iron, cast steel and acid- and heat-resistant steels
- Manufactured to DIN 338 N
- High-speed steel (HSS) with 5% Cobalt
- Long lasting performance
- Top angle 135°
- Split-Point
- Ground flutes enable fast drilling and high precision
- DIN 338N
- Retail pack



Follow the Fish!



PRODUCT ATTRIBUTES

Product	A	B	C	D	
4411-1.00	1.00 mm	34 mm	1.00 mm	12 mm	10 g
4411-1.50	1.50 mm	40 mm	1.50 mm	18 mm	11 g
4411-2.00	2.00 mm	49 mm	2.00 mm	24 mm	12 g
4411-2.50	2.50 mm	57 mm	2.50 mm	30 mm	14 g
4411-3.00	3.00 mm	61 mm	3.00 mm	33 mm	15 g
4411-3.25	3.25 mm	65 mm	3.25 mm	36 mm	17 g
4411-3.30	3.30 mm	65 mm	3.30 mm	36 mm	17 g
4411-3.50	3.50 mm	70 mm	3.50 mm	39 mm	18 g
4411-4.00	4.00 mm	75 mm	4.00 mm	43 mm	22 g
4411-4.20	4.20 mm	75 mm	4.20 mm	43 mm	16 g
4411-4.25	4.25 mm	75 mm	4.25 mm	43 mm	16 g
4411-4.50	4.50 mm	80 mm	4.50 mm	47 mm	19 g
4411-5.00	5.00 mm	86 mm	5.00 mm	52 mm	21 g
4411-5.50	5.50 mm	93 mm	5.50 mm	57 mm	24 g
4411-6.00	6.00 mm	93 mm	6.00 mm	57 mm	26 g
4411-6.50	6.50 mm	101 mm	6.50 mm	63 mm	33 g
4411-6.80	6.80 mm	109 mm	6.80 mm	69 mm	37 g
4411-7.00	7.00 mm	109 mm	7.00 mm	69 mm	37 g
4411-7.50	7.50 mm	109 mm	7.50 mm	69 mm	41 g
4411-8.00	8.00 mm	117 mm	8.00 mm	75 mm	48 g
4411-8.50	8.50 mm	117 mm	8.50 mm	75 mm	52 g
4411-9.00	9.00 mm	125 mm	9.00 mm	81 mm	61 g
4411-9.50	9.50 mm	125 mm	9.50 mm	87 mm	62 g
4411-10.00	10.00 mm	125 mm	10.00 mm	87 mm	74 g
4411-10.20	10.20 mm	133 mm	10.20 mm	87 mm	77 g
4411-10.50	10.50 mm	133 mm	10.50 mm	87 mm	74 g
4411-11.00	11.00 mm	142 mm	11.00 mm	94 mm	94 g
4411-11.50	11.50 mm	142 mm	11.50 mm	94 mm	92 g
4411-12.00	12.00 mm	151 mm	12.00 mm	101 mm	115 g
4411-12.50	12.50 mm	151 mm	12.50 mm	101 mm	110 g
4411-13.00	13.00 mm	151 mm	13.00 mm	101 mm	130 g

Follow the Fish!



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hand Tools](#) category:

Click to view products by [Bahco](#) manufacturer:

Other Similar products are found below :

[58284-1](#) [662908-1](#) [68764-0001](#) [690619-6](#) [D20419-189](#) [7-354778-7](#) [768531-1](#) [821903-5](#) [822253-1](#) [854183-1](#) [854358-1](#) [992258-1](#) [1-21046-3](#)
[1-22278-0](#) [1-22278-2](#) [1-24954-2](#) [125529-5](#) [126513-1](#) [1-305579-8](#) [1320846-1](#) [1338618-1](#) [1338968-2](#) [1-354779-0](#) [1-354779-2](#) [1-354779-4](#)
[1424443-1](#) [1424289-1](#) [1424444-1](#) [MS24256A16](#) [1-525442-0](#) [1532195-2](#) [1538773-2](#) [1-59907-5](#) [1-692134-3](#) [HT-920A-124-HTELE-RPL-KIT](#)
[1976923-1](#) [1976969-1](#) [2063794-1](#) [2063795-1](#) [2-21002-1](#) [2-21002-3](#) [2-21002-4](#) [2-21002-7](#) [2-21002-9](#) [2-21004-0](#) [229399-2](#) [229707-1](#)
[911737-2](#) [2598-5027-54](#) [91348-2](#)