

# DBQ5 Portable Demo Box

- Used to power dc self-contained photoelectric sensors for testing purposes
- Designed around the 4-pin euro-style connector
- Powered by three standard 9V batteries (27V dc) for very long service life
- Features bi-color LEDs which indicate not only sensor output status, but also output type (NPN or PNP)
- Cable adapters are available to convert to pico-style or mini-style connectors
- A 4-pin wiring barrier is mounted on the top of the box to allow connection of cabled dc sensors



## Demo Box

Model	Dimensions
DBQ5	114 mm wide x 62 mm deep x 47 mm high (4.5" x 2.4" x 1.9")

## Cable Adapters

Part Number	Type	Used for:
39536	Euro-to-pico	D11, D12, Q23, S12, MINI-BEAM2 and PICO-AMP series sensors
39537	Euro-to-mini	VALU-BEAM, Q45 series, SM30 dc series OPTO-TOUCH and OMNI-BEAM sensors

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [banner manufacturer](#):*

Other Similar products are found below :

[Q45VR2FPQ](#) [BTA23S](#) [RS-11](#) [L16F](#) [2LM3](#) [2PBA](#) [LM8-1](#) [LMT](#) [SM312CV](#) [SM31RQD](#) [LS4ELQ](#) [FX1](#) [Q45BB6LLQ](#) [QM42VP6AFV150Q](#)  
[D12SP6FP](#) [MBCC-412](#) [BA23S](#) [BT21S](#) [BTA13S](#) [LM4-2](#) [Q25SP6LPQ](#) [ES-FA-6G](#) [T183E](#) [SLSP30-600Q88](#) [SLSP30-1200Q88](#) [OPBA5](#)  
[PBAT](#) [SBLV1](#) [SMA91EQD](#) [SMA91E](#) [SMA912LVQD](#) [SMA912DQD](#) [SM2A312CVQD](#) [SM2A912LVQD](#) [SM31RL](#) [TL70RAQ](#) [TL70RQ](#)  
[K50LGRYPQ](#) [LEDRR70X70-78587](#) [BRT-THG-4X4-5](#) [T18-2VNDL-Q8](#) [SLLP14-1190P88](#) [SME312DQD](#) [SM312CUQD](#) [BR-2](#) [BR23P](#)  
[SM2A312FPQD](#) [SM2A312LVQD](#) [SM31EQD](#) [D12EP6FP](#)