

型番	Product Name	CF16ZA-1S
焦点距離 [mm]	Focal length [mm] (design value)	16 (16.42)
絞り範囲 (F値)	Iris range (Fnumber)	F1.8-F16
画角 (H × V)	Angle of view	47.3° × 36.1° (1.1")
フォーカス範囲 (レンズメカ先端より) [mm]	Working distance (from front of lens barrel) [mm]	∞ - 100
操作方法:フォーカス	Operation of focus	Manual
操作方法:アイリス	Operation of iris	Manual
フィルタ径 [mm]	Filter thread [mm]	M37.5 × 0.5
マウント	Mount	C-mount
質量 (約) [g]	Weight (approx.) [g]	180
適合センサーサイズ (標準)	Sensor size (std.)	1.1" (2.5μm)
適合センサーサイズ (最大)	Sensor size (max.)	1.2" (2.74μm)
バックフォーカス (空気換算長) [mm]	Back focal length (in air) [mm]	21,85
フランジバック [mm]	Flange back [mm]	17,53
入射瞳位置 (マウント面から) [mm]	Entrance pupil position (from Mount) [mm]	-48,25
射出瞳位置 (結像面より) [mm]	Exit pupil position (from image plane) [mm]	-88,43
前側主点 (マウント面から) [mm]	Front principal point (from Mount) [mm]	-35,21
後側主点 (マウント面から) [mm]	Rear principal point (from Mount) [mm]	1,10
主点間隔 [mm]	Distance between the principal points [mm]	36,31
TVディストーション [%]	TV distortion [%]	-0,8
外形寸法 [mm]	Dimension [mm]	φ39 × 67.6
主光線入射角度 [°]	Chief Ray Angle [°]	4,93
周辺光量比 (F4.0・対角端) [%]	Relative illumination [%] (Aperture: F4.0, Image height : at diagonal)	92
周辺光量比 (開放・対角端) [%]	Relative illumination [%] (Aperture: at full open, Image height : at diagonal)	36
使用温度範囲	Operation Temperature Range	-10°C ~ +50°C
保存温度範囲	Storage Temperature Range	-30°C ~ +60°C

These specifications are subject to change without notice.

1-Sep-20

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Camera Lenses](#) category:

Click to view products by [Basler](#) manufacturer:

Other Similar products are found below :

[114992275](#) [114992276](#) [114992278](#) [2000024600](#) [2000030497](#) [2000034588](#) [2000034589](#) [2000034590](#) [2000034591](#) [2000034697](#) [2000034698](#)
[2000034700](#) [2000034703](#) [2000034830](#) [2000034831](#) [2000034832](#) [2000034833](#) [2000034834](#) [2000034835](#) [2000034903](#) [2000034904](#)
[2000035065](#) [2000035175](#) [2000035176](#) [2000035177](#) [2000035178](#) [2000035179](#) [2000035180](#) [2000035181](#) [2000035183](#) [2000035184](#)
[2000035187](#) [2000035189](#) [2000035190](#) [2000035191](#) [2000035192](#) [2000035198](#) [2000035612](#) [2000035614](#) [2000035615](#) [2000036060](#)
[2000036061](#) [2000036374](#) [2000036376](#) [2000036377](#) [2000036378](#) [2000036379](#) [2000036380](#) [2000036382](#) [2000036384](#)