

# Industrial Ethernet Surge Suppressor

– 60V protection on all Ethernet lines

Model BB-EIRSP1

# ADVANTECH

[www.advantech.com](http://www.advantech.com)



## PRODUCT FEATURES

- Single-stage surge protection for all eight Cat5e lines
- 10/100 BaseT Ethernet, RJ45 connectors
- Wide operating temperature (-40 to +80 °C)
- DIN rail mount IP30 enclosure
- Power-over-Ethernet (PoE) compatible
- UL Listed

Model BB-EIRSP1, Industrial Ethernet Surge Suppressor, is designed to protect all eight lines of a standard Cat5e Ethernet cable. It is compatible with 10/100BaseT networks and 802.11af (Modes A & B) Power-over-Ethernet ("PoE"). Mode A applies power to the data pairs, pins 1/2 and 3/6. Mode B applies power to the unused pairs, pins 4/5 and 7/8.

Network connections are made using RJ-45 connectors. Grounding is accomplished using a ground lug which accepts 14 to 22 AWG wire. Stranded or braided cable is recommended with a 1 meter (3 ft) maximum run to Earth Ground.

## ORDERING INFORMATION

MODEL NUMBER	
BB-EIRSP1	Industrial Ethernet Surge Suppressor, Single Stage

## SPECIFICATIONS

NETWORK	
Ethernet Connector	RJ45 (In and Out)
Protocols	PoE 802.11af (Power-over-Ethernet) (Modes A & B)
Speed	10/100 BaseT
SURGE PROTECTION	
Lines Protected	All eight (8) RJ45 (CAT5)
Clamping Voltage	60V
Peak Pulse Power	600 W
Peak Surge Current	1000 Amps
Capacitance	<50 pF
ENVIRONMENTAL	
Response Time	<5 ns
Operating Temperature	-40 to +80 °C (-40 to +176 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Operating Humidity	0 to 95%, non-condensing
PHYSICAL	
Enclosure	Plastic, IP30
Mounting	DIN Rail
Dimensions	3.0 x 11.9 x 8.6 cm (1.2 x 4.7 x 3.4 in)
WIRING	
Wire Type	Copper wire only. One conductor per terminal.
Wire Range	14 to 22 AWG
Tightening Torque	1.7 lb-in
Wire Temperature Rating	105 °C, max. (sized for 60 °C ampacity)
MEANTIME BETWEEN FAILURE (MTBF)	
MTBF	1275588 hours
MTBF Calc. Method	MIL117F Parts Count Reliability Prediction
CERTIFICATIONS	
CE, FCC, UL Listed	
CE - Directives	2014/30/EU Electromagnetic Compatibility Directive 2011/65/EU amended by (EU) 2015/863 Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU Waste Electrical and Electronic Equipment (WEEE)
Ce - Standards	<b>EMC:</b> EN 55032:2015 Class A Electromagnetic compatibility of multimedia equipment – Emission requirements EN 55024:2010 Information Technology Equipment – Immunity Characteristics – Limits and methods of measurement

All product specifications are subject to change without notice.  
BB-EIRSP1\_pn8440\_r2\_2320s

# ADVANTECH

Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | [orders@advantech-bb.com](mailto:orders@advantech-bb.com) | [support@advantech-bb.com](mailto:support@advantech-bb.com)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Surge Suppressors](#) category:*

*Click to view products by [B&B Electronics](#) manufacturer:*

Other Similar products are found below :

[GUS1](#) [GUS12](#) [BSPM1A600D600LVR](#) [2800521](#) [29-2053](#) [GUS11](#) [GUS2](#) [GUS3](#) [GUS4](#) [30460](#) [SRA64C060X](#) [PC642C015](#) [1810-15-A3](#)  
[2713175](#) [4B06B-EC1-150LF](#) [SRA6LC](#) [BPMA75D100LV](#) [CX06M](#) [CCTV1](#) [GUS13](#) [GUS14](#) [GUS5](#) [GUS6](#) [VAL-MS 320/3+0-FM](#) [VAL-US-](#)  
[120/40/1+1-FM](#) [VAL-US-120/65/1+1-FM](#) [VAL-US-480D/30/3+0-FM](#) [VAL-US-120/40/1+0-FM](#) [STCHSP121BT1RU](#) [LP-STRL-NFF](#) [LP-](#)  
[STRL-DFE](#) [GUS22](#) [0804111](#) [5053609](#) [5053201](#) [SPD2-150-1P0](#) [SPD2-550-1P0](#) [6720005416](#) [6720005417](#) [1-2191595-2](#) [STC-CAT6-P0E-I](#)  
[SPD2-350-1P0](#) [FLT-CP-350-ST](#) [TTC-6P-3-HF-F-M-12DC-UT-I](#) [SMTPA200](#) [2800989](#) [2906776](#) [2906810](#) [2906847](#) [2906848](#)