C6015-0010 | Ultra-compact industrial PC

Intel Atom® with up to four cores

Variants	Processor	available
C6015-0020	Intel Atom®, 2 Cores (TC3: 40*) or Intel Atom®, 4 Cores (TC3: 50*)	May 2020
C6015-0010	Intel Atom®, 1 Core (TC3: 40*), Intel Atom®, 2 Cores (TC3: 40*) or Intel Atom®, 4 Cores (TC3: 50*)	yes

^{*}The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see here for an overview of the TC3 performance classes.

C6015-0010	Fanless control cabinet PC
Housing	fanless industrial PC for space-saving control cabinet installation
	mounting plate on the rear wall
	all connectors on the same level
	flexible mounting mechanism for the free alignment of the connecting area
	aluminium zinc die-cast housing
	status LEDs
	lithium battery easily accessible
	1 slot for one M.2 SSD easily accessible
	passive, fanless cooling with one-sided cool plate
	5 cm (2") free space on top and bottom of the PC necessary for air circulation
	protection class IP 20
	operating temperature 055 °C
	compact dimensions (W x H x D) 82 x 82 x 40 mm (3.2" x 3.2" x 1.6"), without mounting plate
Features	Intel Atom® E3815, 1.46 GHz, 1 core (TC3: 40)
	compact motherboard for Intel Atom® E38xx
	2 GB DDR3L RAM, expandable ex factory to 4 GB
	graphic adapter integrated inside the Intel® processor, 1 DisplayPort connector
	on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector
	40 GB M.2 SSD, 3D flash, extended temperature range
	1 USB 3.0 port and 1 USB 2.0 port
	24 V DC power supply
	Microsoft Windows Embedded Compact 7, English

Options	C6015-0010
C9900-C582	processor Intel Atom® E3827, 1.75 GHz, 2 cores (TC3: 40) and memory extension to 4 GB DDR3L RAM instead of Intel Atom ® E3815, 1.46 GHz (TC3: 40) and 2 GB DDR3L RAM main memory. Memory extension requires a 64 bit operating system or only 3 GB are addressable. With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 IoT Enterprise.
C9900-C583	processor Intel Atom® E3845, 1.91 GHz, 4 cores (TC3: 50) and memory extension to 4 GB DDR3L RAM instead of Intel Atom ® E3815, 1.46 GHz (TC3: 40) and 2 GB DDR3L RAM main memory. Memory extension requires a 64 bit operating system or only 3 GB are addressable. Operating temperature range 050 °C With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 loT Enterprise.
C9900-H591	80 GB M.2 SSD, 3D flash, extended temperature range, for C601x, instead of 40 GB M.2 SSD
C9900-H599	160 GB M.2 SSD, 3D flash, extended temperature range, for C601x, instead of 40 GB M.2 SSD
C9900-Z468	adapter cable DisplayPort to DVI, 40 cm
C9900-M664	mounting plate for C601x at the side wall, instead of plate at the rear wall
C9900-M665	mounting plate for lateral installation of the C601x; single part, not mounted
C9900-M666	mounting plate with DIN rail mounting adapter for C601x, instead of standard mounting plate
C9900-M667	mounting plate with DIN rail mounting adapter for C601x; single part, not mounted
C9900-S706	TwinCAT 2 PLC runtime for Windows Embedded Compact 7
C9900-S707	TwinCAT 2 NC PTP runtime for Windows Embedded Compact 7
C9900-S708	TwinCAT 2 NC I runtime for Windows Embedded Compact 7

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Beckhoff manufacturer:

Other Similar products are found below:

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03 HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K 26546803 26546805 26546831 CJ1W-OD204