



Top view

## EL6601 | Ethernet switch port terminal

The EL6601 Ethernet switch port terminal is used for the decentralised connection of Ethernet devices to the EtherCAT Terminal network. The EtherCAT system relays the Ethernet communication of the connected devices fully transparent and collision-free.

The switch port terminal can be installed at any location within the EtherCAT strand. No configuration is required.

Further benefits underline the particular suitability for the application in industrial environments:

- compact design in EtherCAT Terminal housing
- 10/100 Mbaud, half or full duplex, with automatic baud rate detection
- support for network variables

| Technical data                     | EL6601   |
|------------------------------------|--|
| Number of Ethernet ports           | 1  |
| Bus system                         | all Ethernet (IEEE 802.3)-based protocols, store and forward switching mode  |
| Ethernet interface                 | 10BASE-T/100BASE-TX Ethernet with 1 x RJ45   |
| Data transfer rates                | 10/100 Mbit/s, IEEE 802.3u auto-negotiation, half or full duplex at 10 and 100 Mbit/s possible, automatic settings |
| Cable length                       | up to 100 m twisted pair   |
| Hardware diagnosis                 | status LEDs  |
| Power supply                       | via the E-bus  |
| Distributed clocks                 | –  |
| Electrical isolation               | 500 V (E-bus/Ethernet)   |
| Protocol                           | all Ethernet (IEEE 802.3)-based protocols, store and forward switching mode  |
| Configuration                      | no   |
| Current consumption power contacts | –  |
| Current consumption E-bus          | typ. 310 mA  |
| Special features                   | support of RT Ethernet, publisher/subscriber, DHCP/BootP address allocation (1 device)                             |
| Weight                             | approx. 75 g   |
| Operating/storage temperature      | -25...+60 °C/-40...+85 °C  |
| Relative humidity                  | 95 %, no condensation  |
| Vibration/shock resistance         | conforms to EN 60068-2-6/EN 60068-2-27   |
| EMC immunity/emission              | conforms to EN 61000-6-2/EN 61000-6-4  |
| Protect. class/installation pos.   | IP 20/variable   |
| Approvals                          | CE, UL, Ex, IECEx  |

| System          |   |
|-----------------|---|
| Ethernet TCP/IP | For further Ethernet TCP/IP products please see the <a href="#">system overview</a> . |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Controllers](#) category:*

*Click to view products by [Beckhoff](#) manufacturer:*

Other Similar products are found below :

[CS1WCN223](#) [CS1WCN713](#) [CS1WKS001E](#) [61F-11NH](#) [61FGPN8DAC120](#) [61F-GP-NT AC110](#) [61F-GPN-V50-AC110](#) [70177-1011](#) [F03-03](#)  
[HAS B](#) [F03-03 HAS C](#) [F03-31](#) [81513201](#) [81513535](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [R88A-CAGA005S](#) [R88A-](#)  
[CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [DTB4896VRE](#) [DTB9696CVE](#) [DTB9696LVE](#) [MR-50LF+](#) [E53-AZ01](#) [E53E8C](#)  
[E5CWLQ1TCAC100240](#) [B300LKL21](#) [NE1ASCPU02EIPVER11](#) [NE1SCPU01](#) [NE1SDRM21U](#) [NSCXDC1V3](#) [NSH5-232CW-3M](#)  
[NT20SST122BV1](#) [NV3Q-SW41](#) [NV4W-ATT01](#) [NV-CN001](#) [OAS-160-N](#) [K31S6](#) [K33-L1B](#) [K3TX-AD31A](#) [L595020](#) [SRS2-1](#) [G32X-V2K](#)  
[26546803](#) [26546805](#) [26546831](#) [CJ1W-OD204](#)