

KL1002 | 2-channel digital input terminal 24 V DC

The KL1002 digital input terminal acquires the binary control signals from the process level and transmits them, in an electrically isolated form, to the higher-level automation unit. The Bus Terminal contains two channels that indicate their signal state by means of light emitting diodes.

Technical data	KL1002 KS1002
Connection technology	4-wire
Specification	EN 61131-2, type 1/3
Number of inputs	2
Nominal voltage	24 V DC (-15 %/+20 %)
"0" signal voltage	-3+5 V
"1" signal voltage	1530 V
Input filter	typ. 3.0 ms
Input current	typ. 5 mA
Current consumption K-bus	typ. 3 mA
Electrical isolation	500 V (K-bus/field potential)
Bit width in the process image	2 inputs
Configuration	no address or configuration setting
Weight	approx. 50 g
Operating/storage temperature	-25+60 °C/-40+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all KSxxxx Bus Terminals
Approvals	CE, UL, Ex, GL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Beckhoff manufacturer:

Other Similar products are found below:

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03 HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K 26546803 26546805 26546831 CJ1W-OD204