

KL9110 | Potential supply terminal, 24 V DC, with diagnostics

The KL9110 power feed terminal makes it possible to set up various potential groups with the standard voltage of 24 V DC. In order to monitor the supply voltage, the terminal with diagnostics reports the status of the power feed terminal to the Bus Coupler through two input bits. It is thus possible for the controller to check the distributed peripheral voltage over the fieldbus.

Technical data	KL9110 KS9110
Nominal voltage	24 V DC
Current load	≤ 10 A
Integrated fine-wire fuse	-
Diagnostics	yes
Power LED	green
Defect LED	-
Reported to K-bus	yes
PE contact	yes
Shield connection	-
Renewed infeed	yes
Connection facility to additional power contact	1
K-bus, looped through	yes
Bit width in the process image	1
Electrical connection to DIN rail	-
Current consumption K-bus	typ. 10 mA
Electrical isolation	yes
Housing width in mm	12
Weight	approx. 50 g
Side by side mounting on Bus Terminals with power contact	yes
Side by side mounting on Bus Terminals without power contact	yes
Operating/storage temperature	-25+60 °C/-40+85 °C
Pluggable wiring	for all KSxxxx Bus Terminals
Approvals	CE, UL, Ex, GL, IECEx

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Controllers category:

Click to view products by Beckhoff manufacturer:

Other Similar products are found below:

CS1WCN223 CS1WCN713 CS1WKS001E 61F-11NH 61FGPN8DAC120 61F-GP-NT AC110 61F-GPN-V50-AC110 70177-1011 F03-03 HAS B F03-03 HAS C F03-31 81513201 81513535 81550401 FT1A-C12RA-W 88981106 H2CAC24A R88A-CAGA005S R88A-CRGB003CR-E R88ARR080100S R88A-TK01K DCN1-1 DTB4896VRE DTB9696CVE DTB9696LVE MR-50LF+ E53-AZ01 E53E8C E5CWLQ1TCAC100240 B300LKL21 NE1ASCPU02EIPVER11 NE1SCPU01 NE1SDRM21U NSCXDC1V3 NSH5-232CW-3M NT20SST122BV1 NV3Q-SW41 NV4W-ATT01 NV-CN001 OAS-160-N K31S6 K33-L1B K3TX-AD31A L595020 SRS2-1 G32X-V2K 26546803 26546805 26546831 CJ1W-OD204