



KL9200 | Potential supply terminal, 24 V DC, with fuse

The KL9200 power feed terminal makes it possible to set up various potential groups with the standard voltage of 24 V DC.

Technical data	KL9200
Nominal voltage	24 V DC
Current load	≤ 10 A
Integrated fine-wire fuse	...6.3 A
Diagnostics	–
Power LED	green
Defect LED	red
Reported to K-bus	–
PE contact	yes
Shield connection	–
Renewed infeed	–
Connection facility to additional power contact	1
K-bus, looped through	yes
Bit width in the process image	0
Electrical connection to DIN rail	–
Current consumption K-bus	–
Electrical isolation	yes
Housing width in mm	12
Special features	integrated fuse
Weight	approx. 50 g
Side by side mounting on Bus Terminals with power contact	yes
Side by side mounting on Bus Terminals without power contact	yes
Operating/storage temperature	0...+55 °C/-25...+85 °C
Approvals	CE, UL, Ex, GL

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Controllers](#) category:

Click to view products by [Beckhoff](#) manufacturer:

Other Similar products are found below :

[CS1WCN223](#) [CS1WCN713](#) [CS1WKS001E](#) [61F-11NH](#) [61FGPN8DAC120](#) [61F-GP-NT AC110](#) [61F-GPN-V50-AC110](#) [70177-1011](#) [F03-03](#)
[HAS B](#) [F03-03 HAS C](#) [F03-31](#) [81513201](#) [81513535](#) [81550401](#) [FT1A-C12RA-W](#) [88981106](#) [H2CAC24A](#) [R88A-CAGA005S](#) [R88A-](#)
[CRGB003CR-E](#) [R88ARR080100S](#) [R88A-TK01K](#) [DCN1-1](#) [DTB4896VRE](#) [DTB9696CVE](#) [DTB9696LVE](#) [MR-50LF+](#) [E53-AZ01](#) [E53E8C](#)
[E5CWLQ1TCAC100240](#) [B300LKL21](#) [NE1ASCPU02EIPVER11](#) [NE1SCPU01](#) [NE1SDRM21U](#) [NSCXDC1V3](#) [NSH5-232CW-3M](#)
[NT20SST122BV1](#) [NV3Q-SW41](#) [NV4W-ATT01](#) [NV-CN001](#) [OAS-160-N](#) [K31S6](#) [K33-L1B](#) [K3TX-AD31A](#) [L595020](#) [SRS2-1](#) [G32X-V2K](#)
[26546803](#) [26546805](#) [26546831](#) [CJ1W-OD204](#)