



**Product:** [1326A](#) 

Security & Sound, 3 Pair 22 AWG BC, Individually Shielded, CMP



## Product Description

Security & Commercial Audio Cable, 3 Pair 22 AWG stranded bare copper pairs with Flamarrest® insulation, individually Beldfoil® shields, Plenum-CMP, Flamarrest® jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Sound and Audio Systems, Intercom and PA Systems, Security Systems, Access Control Systems, Power-Limited Control Systems
------------------------	---

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	3

Conductor Count:	6
Total Number of Pairs:	3

#### Insulation

Material	Material Trade Name
PVC - Polyvinyl Chloride	Flamarrest®

#### Color Chart

Number	Color
1	Black & Red
2	Black & Green
3	Black & White

#### Inner Shield

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Bi-Laminate (Alum+Poly)	Beldfoil® (Z-Fold®)	100%	TC - Tinned Copper	24	7x32

#### Outer Shield

Material
No Shield

#### Outer Jacket

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Flamarrest®	0.19 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor Loop DCR	Nominal Inner Shield DCR
14.7 Ohm/1000ft	8.6 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor

34 pF/ft

#### Current

##### Max. Recommended Current [A]

2.8 Amps per Conductor at 25°C

#### Voltage

##### UL Voltage Rating

300 V RMS

#### Temperature Range

Operating Temp Range: 0°C To +75°C

#### Mechanical Characteristics

Bulk Cable Weight: 26 lbs/1000ft

Max. Pull Tension: 60 lbs

Min. Bend Radius/Minor Axis: 1.9 in

#### Standards

NEC/(UL) Compliance: CMP

CEC/C(UL) Compliance: CMP

CPR Euroclass: Eca

#### Applicable Environmental and Other Programs

Environmental Space: Indoor - Plenum

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (RoHS 2): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU (RoHS 2 amendment): Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

MII Order #39 (China RoHS): Yes

#### Suitability

Suitability - Indoor: Yes

#### Flammability, LSOH, Toxicity Testing

C(UL) Flammability: FT6

UL Flammability: UL910 Steiner Tunnel

IEC Flammability: IEC 60332-1-2

UL voltage rating: 300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N): Yes

#### Part Number

Non-Plenum Number: 8777

#### Variants

Item #	Color	Put-Up Type	Length	UPC
1326A D15500	Blue	Reel	500 ft	612825111979
1326A D151000	Blue	Reel	1,000 ft	612825111962
1326A 009500	White	Reel	500 ft	612825111993
1326A 0091000	White	Reel	1,000 ft	612825111986
1326A 009Z1000	White	ReelTuff Box	1,000 ft	612825426615

Footnote: C - CRATE REEL PUT-UP.

#### History

Update and Revision: Revision Number: 0.374 Revision Date: 08-27-2021

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#) [CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#) [CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-1000](#) [8125-CHR-100](#) [8164-CHR-1000](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#) [83009-VIO-100](#)