




**Product:** [1624R](#) 

Category 5 Cable, 4 Pair, F/UTP, CMR

### Product Description

Category 5 Premise Horizontal Cable (100MHz), 4 Pairs, 24 AWG Solid Bare Copper Conductors, F/UTP - Foil Shielded, Riser-CMR, PVC Jacket

### Technical Specifications

#### Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet 1000BASE-T, Ethernet 100BASE-TX, Ethernet 10BASE-T, PoE++, PoE+, PoE , Noisy Environments
------------------------	--

#### Construction Details

##### Conductor

Size	Stranding	Material	Number of Pairs
24 AWG	Solid	BC - Bare Copper	4

##### Insulation

Material	Color Code
PO - Polyolefin	White/Blue Stripe & Blue, White /Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown

##### Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Polyester + Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

##### Outer Jacket

Material	Nom. Diameter	Ripcord
PVC - Polyvinyl Chloride	0.26 in (6.6 mm)	No

#### Electrical Characteristics

##### Electricals

Max. Conductor DCR
93.8 Ohm/km

##### Delay

Max. Delay	Max. Delay Skew	Nom. Velocity of Prop.
538 ns/100m	45 ns/100m	67%

##### High Frequency

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. SRL (Structural Return Loss) [dB]	Max./Min. Fitted Impedance
1	2.0 dB/100m	62.2	62.3	23	100 ± 15 Ohm
4	4.1 dB/100m	53.3	53.3	23	100 ± 15 Ohm
8	5.8 dB/100m	48.8	48.8	23	100 ± 15 Ohm
10	6.5 dB/100m	47.3	47.3	23	100 ± 15 Ohm
16	8.2 dB/100m	44.3	44.3	23	100 ± 15 Ohm
20	9.3 dB/100m	42.8	42.8	23	100 ± 15 Ohm
25	10.4 dB/100m	41.3	41.3	22	100 ± 15 Ohm
31.25	11.7 dB/100m	39.9	39.9	21.1	100 ± 15 Ohm
62.5	17.0 dB/100m	35.4	35.4	18	100 ± 15 Ohm

100	22.0 dB/100m	32.2	32.3	16	100 ± 15 Ohm
-----	--------------	------	------	----	--------------

## Voltage

<b>UL Voltage Rating</b>
300 V (CMR)

## Mechanical Characteristics

### Temperature

<b>Operating</b>
-20°C To +75°C

### Bend Radius

<b>Stationary Min.</b>	<b>Installation Min.</b>
1 in (25 mm)	2.6 in (66 mm)

Max. Pull Tension:	25 lbs (11 kg)
Bulk Cable Weight:	30 lbs/1000ft

## Standards and Compliance

Environmental Suitability:	Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, FT4, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMR
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3
Data Category:	Category 5
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	1624P

## Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Shield is bonded to jacket inner wall for electrical stability. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5.
--------	--

## History

Update and Revision:	Revision Number: 0.286 Revision Date: 12-22-2021
----------------------	--

## Variants

Item #	Color	Putup Type	Length	UPC
1624R 0061000	Blue	Reel	1,000 ft	612825119623
1624R 006A1000	Blue	Reel-in-Box	1,000 ft	612825119616
1624R F2V1000	Gray	Reel	1,000 ft	612825119517
1624R F2VA1000	Gray	Reel-in-Box	1,000 ft	612825119500
1624R F2V1640	Gray	Reel	1,640 ft	612825119524
1624R 0051000	Green	Reel	1,000 ft	612825119609
1624R 005A1000	Green	Reel-in-Box	1,000 ft	612825119593
1624R 0031000	Orange	Reel	1,000 ft	612825119562
1624R 003A1000	Orange	Reel-in-Box	1,000 ft	612825119555
1624R B021000	Purple	Reel	1,000 ft	612825119494
1624R B02A1000	Purple	Reel-in-Box	1,000 ft	612825119487
1624R 0021000	Red	Reel	1,000 ft	612825119548
1624R 002A1000	Red	Reel-in-Box	1,000 ft	612825119531
1624R 0041000	Yellow	Reel	1,000 ft	612825119586
1624R 004A1000	Yellow	Reel-in-Box	1,000 ft	612825119579

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[8916-GRY-100](#) [8917-BLK-100](#) [8918-GRN/YEL-100](#) [8920-BRN-1000](#) [8920-RED-1000](#) [89907-LT-DEC/GRY-500](#) [CR3909-000](#) [CR3927-000](#) [01342.35T.01](#) [01364.35T.01](#) [CS2885-000](#) [CS8782-000](#) [CS9912-000](#) [6200UE-NAT-U1000](#) [CTC-0062-20-9/5-9](#) [CTC-0062-22-9/5-9](#) [6304FE-877-U500](#) [6309UE-877-1000](#) [6320UE-NAT-U1000](#) [644833-000](#) [6502FE 8771000](#) [6504UE-877-U1000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [706/2R-BLACK-EACH](#) [720451-000](#) [730859-000](#) [MCC-USB-4-250](#) [752687-000](#) [768146-000](#) [773159-000](#) [7934A-BLK-1000](#) [8125-CHR-100](#) [8164-CHR-1000](#) [820457-000](#) [8205-CHR-1000](#) [8240-BLK-U1000](#) [82723-NAT-1000](#) [82907-NAT-500](#) [83003-YEL-500](#) [83005-WHT-500](#) [83006-DK-GRN-100](#) [83008-WHT-1000](#) [83009-BLK-100](#)