

100

Product: <u>1862A</u> ☑

Speaker Cable, 2 Conductor 16 AWG BC, Unshielded, CMP

Product Description

Speaker Cable, 2 Conductor 16 AWG stranded (19x29) high conductivity bare copper conductors with Flamarrest® insulation, cabled in an open twisted construction, Plenum-CL3P.

Technical Specifications

Product Overview Suitable Applications: Speaker Cable **Physical Characteristics (Overall)** Conductor AWG Stranding Material No. of Conductors BC - Bare Copper 2 19x29 16 2 Conductor Count: Insulation Material Trade Name Nominal Wall Thickness Material PVC-LS - Polyvinyl Chloride (Low Smoke) Flamarrest® 0.022 in Outer Shield Material Material No Shield **Outer Jacket Material** Nominal Diameter 0.202 in **Electrical Characteristics** Conductor DCR Nominal Conductor DCR 4.2 Ohm/1000ft Inductance Nominal Inductance 0.186 µH/ft Current Max. Recommended Current [A] 6.5 Amps per Conductor at 25°C

Voltage

UL Voltage Rating 150 V RMS

Temperature Range

Non-UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	24 lbs/1000ft
Max. Pull Tension:	60.8 lbs
Min Bend Radius/Minor Axis:	2.25 in

Standards

NEC/(UL) Compliance:	CL3P

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability -	Indoor:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262
UL voltage rating:	150 V RMS

Plenum/Non-Plenum

	Plenum (Y/N):	Yes
--	---------------	-----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
1862A D261000	Black & Natural Pair	Reel	1,000 ft	612825125167
Footnote:		C - CRA	TE REEL	PUT-UP.
History				

Update and Revision: Revision Number: 0.265 Revision Date: 06-24-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444

 060U1000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 9318-060-1000
 939870-000
 9423
 060U500
 9444