



Product: 1883A ☑

Line Level Audio Cable, 1 Pr #24 Str TC, O/A Foil, PVC Jkt, CMR

Product Description

Line Level Audio Cable, 1 Pair 24 AWG (7 x 32) Tinned Copper, PP insulation, Overall Beldfoil® Shield, PVC Jacket, CMR

Technical Specifications

Product Overview

Suitable Applications:	Line level audio; Low voltage analog signals

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Pair(s)	1	24	7x32	TC - Tinned Copper

Insulation

Element	Material	Thickness [in.]	Color Code
Pair(s)	PP - Polypropylene	0.010	Black & Red

Outer Shield Material

Shield Type	Material	Coverage	Drainwire Type	Notes
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC	Drain wire is inside foil shield.

Outer Jacket Material

Material	Thickness	Nom. Dia	ameter
PVC - Polyvinyl Chloride	0.020 in	0.121 in	
Table Notes:			Jacket a
Cable Diameter (Nominal)	:	(0.121 ir

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capa	citance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Characteristic Impedence	Max. Current
Pair(s)	23.5 Ohm/1000ft	31 pF/ft		58 pF/ft	52 Ohm	2 Amps per conductor @ 25°C
Nom Out	er Shield DCR:		18.5 Ohm/1000ft			

Voltage

UL Voltage Rating 300 V (CMR)

Mechanical Characteristics

Temperature



Bend Radius

Stationary Min.	Installation Min.
1.25 in	1.2 in

Max. Pull Tension:	16 lbs
Bulk Cable Weight:	10 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Fire Resistance:	UL1685 UL Loading, FT4, IEC 60332-1-2
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	For cross-connect use with 1408R (et. al.) Snake Cables.

History

Update and Revision:	Revision Number: 0.283 Revision Date: 08-25-2020	

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

89182-010-1000 6000FE-877-1000 M27500-20SP2S23 6300FE-877-U1000 6309UE-877-1000 6502FE 8771000 6541PA-008-U1000 CV6807-000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 752687-000 82841-877-5000 8348-060-500 83559-002-1000 83653-002-5000 83659-002-1000 83709-002-1000 8404-060-500 8469 060100 8628-060-500 868361-001 8730-060-1000 8737-060-U1000 8747-060-100 8747-060-1000 8747-060-1000 8769-060-1000 8775-060-500 877541-000 8780-060-1000 88444-002-1000 9159-060-500 939870-000 9423 060U500 9444 060U1000 9497 0001000 9515-060-1000 9520-060-1000 9524-060-1000 9546-060-500 9572-002-U500 9774-060-1000 1213F-D15-A1000 1213F-009-A1000