



Product Description

Portable Cordage, 2 Conductor 18AWG (42x34) Bare Copper, PVC Insulation, PVC Outer Jacket, UL Type SVT

Technical Specifications

Construction Details

Element	Number o	f Element	Size	Stranding	Material	
Conductor(s)	2		18 AWG	42x34	BC - Bare Cop	per
nsulation						
Mater	ial	Nom. Thio	ckness	Nom. Insula	tion Diameter	Color Code
PVC - Polyvin	yl Chloride	0.018 in (0	.46 mm)	0.084 in (2.1	mm)	Black, White
Outer Jacket						
Separator	Mat	erial	Nom.	Thickness	Nom. Diamete	er
Paper Tape	PVC - Polyv	vinyl Chloride	e 0.036 i	in (0.91 mm)	0.243 in	
Electrical (Characte	ristics				

Nom. Conductor DCR	Max. Current 10 Amps per Conductor at 25°C (7 Amps over 50 ft)		
6.97 Ohm/1000ft			
	7 Amps per Conductor at 25°C (over 50 ft)		

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature 60°C		
Max. Pull Tension:	42.6 lbs	
Bulk Cable Weight:	32 lbs/1000ft	

Standards and Compliance

Environmental Suitability:	Oil Resistance
Flammability / Reaction to Fire:	FT2
NEC / UL Compliance:	Article 400, SVT
AWM Compliance:	SVT
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Overall Cabling Separator Material: Paper Tape	
History		
Update and Revision:	Revision Number: 0.381 Revision Date: 12-15-2021	
Varianto		

Variants

ltem #	Color	Putup Type	Length	UPC
19140 010250	Black	Reel	250 ft	612825126706
19140 008250	Gray	Reel	250 ft	612825126690

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

01342.35T.01 01364.35T.01 CS2885-000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 644833-000 6500FE-877-1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CY0660-000 730859-000 MCC-USB-4-250 768146-000 773159-000 820457-000 82907-NAT-500 83005-WHT-500 83023-YEL-500 83027-RED-100 83029-GRN-100 8302-CHR-500 83046-RED-100 8305-CHR-100 83333-WHT-100 8334-060-1000 83652-RED-100 8404-060-500 8434-CHR-100 8441-BLK-1000 8450-BLK-1000 8451-GRY-U500 8459-CHR-500 8465-CHR-1000 8466-CHR-1000 8467-CHR-1000 8469 060100 8469-CHR-1000 8471-CHR-1000 8472-BLK-250 8473-CHR-U500 8501-ORG-100 8501-RED-100 8502-GRY-100 8503-WHT/BLU-100 8520-BRN-100 8520-GRY-100 8523-GRY-100 8523-GRY-1000