



Product: <u>19349</u> ☑

Portable Cordage, 3 C #16 Str BC, PVC Ins, PVC Jkt, UL Type SJT

Product Description

Portable Cordage, 3 Conductor 16AWG (65x34) Bare Copper, PVC Insulation, PVC Outer Jacket, UL Type SJT

Technical Specifications

Product Overview							
Suitable Applications: Porta			table cordage and cordage				
Construction Details							
Conductor							
Element	Number o	f Element	Size	Stranding	Material		
Conductor(s)) 3		16	65x34	BC - Bare Copper		
Insulation							
Mate	rial	Nom. Thic	knes	s Nom. In	sulation Diameter	Color Code	
PVC - Polyvi	nyl Chloride	0.033 in (0.	84 mr	n) 0.123 in	(3.12 mm)	Green/Yellow, Black, White	
Outer Jacket							
Separator	Mat	erial	No	m. Thickne	ss Nom. Diamet	er	
Paper Tape	pe PVC - Polyvinyl Chloride		0.0	0.038 in (0.97 mm) 0.34 in (8.6 mm		n)	

Electrical Characteristics

Electricals

Nom. Conductor DCR	Max. Current		
4.4 Ohm/1000ft	13 Amps per Conductor at 25°C		

Voltage

UL Voltage Rating

Mechanical Characteristics

Temperature

UL Temperature 60°C

Bend Radius

Stationary Min.	Installation Mi	in.
3.4 in (86 mm)	3.4 in (86 mm)	
Max. Pull Tension	n:	10
Bulk Cable Weigl	ht:	67

Standards and Compliance

Environmental Suitability: Outdoor, Sunlight Resistance

NEC / UL Compliance:	Article 400, SJT
AWM Compliance:	SJT
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.425 Revision Date: 01-11-2022

Variants

Item #	Color	Putup Type	Length	UPC
19349 010250	Black	Reel	250 ft	612825126935
19349 008250	Gray	Reel	250 ft	612825126928

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927000 01342.35T.01 01364.35T.01 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9
6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000
CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405
CY0660-000 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006DK-GRN-100 83008-WHT-1000 83009-BLK-100 83009-VIO-100