

Product: <u>34017</u> ☑ Lead Wire, #17 Str TC, Silicone Ins, AWM 3123 Request Sample **Product Description** Low Temp Rubber Lead Wire, 17AWG (210x40) Tinned Copper, Silicone Insulation, AWM 3123 600V 150C **Technical Specifications Product Overview** Suitable Applications: mercury switches, internal wiring of appliances, high temperature applications, flexing applications **Physical Characteristics (Overall)** Conductor No. of Conductors AWG Stranding Material 17 210x40 TC - Tinned Copper 1 Conductor Count: 1 Insulation Material Nominal Wall Thickness Silicone Rubber 0.03 in **Electrical Characteristics** Voltage UL Voltage Rating 600 V RMS **Temperature Range Mechanical Characteristics Standards** UL AWM Style Compliance: UL AWM Style 3123

EU Directive 2000/53/EC (ELV): Yes EU Directive 2003/96/EC (BFR): Yes EU Directive 2011/65/EU (RoHS 2): Yes EU Directive 2012/19/EU (WEEE): Yes EU Directive 2015/863/EU (RoHS 2 amendment): Yes EU Directive Compliance: EU Directive 2003/11/EC (BFR) CA Prop 65: Yes MII Order #39 (China RoHS): Yes

Non-UL Temp Rating:	150°C
UL Temp Rating:	150°C

Bulk Cable Weight:	12 lbs/1000ft
Min. Bend Radius/Minor Axis:	0.48 in

Applicable Environmental and Other Programs

Flammability, LS0H, Toxicity Testing

UL voltage rating	L voltage rating:			600 V RMS	600 V RMS		
Plenum/Non	lenum/Non-Plenum						
Plenum (Y/N):				No			
Part Number	art Number						
Variants							
ltem #	Color	Put-Up Type	Length	UPC			
34017 0082000	Gray	Reel	2,000 ft	612825143598			
Footnote:	Footnote: C - CRATE REEL PUT-UP.						
History							
Update and Rev	Update and Revision: Re			Revision Numb	per: 0.363 Revision Date: 12-15-2021		

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory and regulatory because the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 7053-RED-1000
 7053-SLATE-1000
 F25935-000
 F60898-000
 8055

 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83005-LT-BLU-1000
 83025-VIO-1000
 8523-RED-100
 8524-WHT-100
 8525

 ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100
 138498-000
 E76065-000
 EPD50886A

 20-9
 BFWUL3239-24-PINK
 C2015A.12.04
 C2015A.12.05
 C2015A.12.08
 C2015A.12.10
 C2016A.12.05
 C2016A.12.07

 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-YEL-100
 8920-YEL-100
 9242833001
 933205-000
 2841/7

 YELLOW-1000
 2842/7-ORANGE-100
 2843/19-BLUE-100
 2843/1-YELLOW-100
 2844/7-BLACK-1000
 2845/7-RED

 100
 2855/1-BLACK-100
 2845/7-RED-1000
 2843/19-BLUE-100
 2843/1-YELLOW-100
 2844/7-BLACK-1000