

| Lead Wire, #12 Str TC, CSPE Ins, AWM 3191 | Product: <u>34412</u> ⊠ | |
|---|---------------------------|------------------|
| the Descuent Controls | Lead Wire, #12 Str TC, CS | PE Ins, AWM 3191 |
| | Request Sample | |

Product Description

Low Temp Rubber Lead Wire, 12AWG (65x30) Tinned Copper, CSPE Insulation, AWM 3191 CSA TYPE CL1053 600V 105C

Technical Specifications

Physical Characteristics (Overall)

| | | • | | |
|---------------------------|-----------------------|-------------------|------------------------|-----------------------------|
| Conductor | | | | |
| AWG Stranding | Material | No. of Conductors | | |
| 12 65x30 | TC - Tinned Copper | 1 | | |
| Conductor Count: | 1 | | | |
| Insulation | | | | |
| Ma | aterial | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
| CSPE - Chlorosul | phonated Polyethylene | 0.19 in | 0.052 in | 0.045 in |
| | | | | |
| Electrical Cha | Iracteristics | | | |
| Voltage | | | | |
| UL Voltage Ratin | 9 | | | |
| 600 V RMS | | | | |
| | | | | |
| Temperature | Range | | | |
| UL Temp Rating: | 105°C | | | |
| Operating Temp F | Range: -30°C To | o +105°C | | |
| Mochanical C | haracteristics | | | |
| | | | | |
| Recommended Ma Cycles: | ax Baking 24 Hour | s @ 300°F (149°C) | | |
| | | | | |

| Bulk Cable Weight: | 35 lbs/1000ft |
|------------------------------|---------------|
| Min. Bend Radius/Minor Axis: | 0.76 in |

Standards

| UL AWM Style Compliance: | UL AWM Style 3191 |
|--------------------------|-------------------|
| CSA Rating: | 600 V, 105°C |
| CSA Type: | CL1053 |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|--------------------------------------|-----|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (RoHS 2): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |

| EU Directive 2015/863/EU (RoHS 2 amendment): | Yes |
|--|-------------------------------|
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| CA Prop 65: | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| | UL voltage rating: | 600 V RMS |
|--|--------------------|-----------|
|--|--------------------|-----------|

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

| Item # | Color | Put-Up Type | Length | UPC |
|---------------|-------------|-------------|----------|--------------------------------------|
| 34412 010100 | Black | Reel | 100 ft | 612825143888 |
| 34412 010500 | Black | Reel | 500 ft | 612825143901 |
| 34412 0103000 | Black | Reel | 3,000 ft | 612825143895 |
| 34412 008500 | Gray | Reel | 500 ft | |
| 34412 005500 | Green, Dark | Reel | 500 ft | 612825143871 |
| 34412 002500 | Red | Reel | 500 ft | 612825143864 |
| Footnote: | | | ANY ON | -UP., F - MAY C E PIECE IS 200'., |

Product Notes

| History | |
|-------------------------------|---|
| Update and Revision: Revision | ion Number: 0.348 Revision Date: 12-15-2021 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 8918-BRN-1000
 8920-DK-BLU-1000
 CR6328-000
 01776.38.01
 M22759/16-14-5-500FT
 7053-RED-1000
 7053-SLATE-1000
 F25935-000

 F60898-000
 8055
 81044/12-18-9CS3209
 82A0811-4-9-G110
 83004-ORG-1000
 83005-LT-BLU-1000
 83025-VIO-1000
 8523-RED-100

 8524-WHT-100
 8525-ORG-1000
 8530-BLK-1000
 8530-LT-BLU-100
 8538-009-1000
 8597-LT-BLU-100
 8898-BLK-100
 138498-000

 E76065-000
 EPD50886A-20-9
 BFWUL3239-24-PINK
 C2015A.12.04
 C2015A.12.05
 C2015A.12.10
 C2015A.12.19

 C2016A.12.05
 C2016A.12.07
 C2065A.12.02
 C77653-000
 220368-001
 8916-GRY-500
 8918-RED-100
 8919-DK-BLU-100
 8919-YEL-100

 8920-YEL-100
 9242833001
 933205-000
 2841/7-YELLOW-1000
 2842/7-ORANGE-100
 2842/7-RED-1000
 2843/19-BLUE-100
 2843/1

 YELLOW-100
 2843/7-GREEN-100
 100
 100
 100
 100
 100
 100
 100