



**Product:** [3633](#) 

Category 6+ Premium Cable, 4 Bonded-Pairs, U/UTP, CMP

## Product Description

Category 6+ Premium Premise Horizontal Cable (400MHz), 4 Bonded-Pairs, 23 AWG Solid Bare Copper Conductors, U/UTP, Plenum-CMP, Flamarrest® PVC-LS Jacket

## Technical Specifications

### Product Overview

Suitable Applications:	Premise Horizontal Cable, Ethernet 1000BASE-T, Ethernet 100BASE-TX, Ethernet 10BASE-T, PoE++, PoE+, PoE
Patent:	This product has one or more applicable patents. More information on patents can be found at <a href="https://www.belden.com/resources/patents">https://www.belden.com/resources/patents</a> .

### Construction Details

#### Conductor

AWG	Stranding	Material	Number of Pairs
23	Solid	BC - Bare Copper	4

#### Insulation

Material	Color Code
FEP - Fluorinated Ethylene Propylene	White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown
Bonded-Pair:	Yes

#### Outer Jacket Material

Separator Material	Material	Material Trade Name	Nom. Diameter	Ripcord
Center Member (Patented X-Spline®)	PVC - Polyvinyl Chloride	Flamarrest®	0.230 in	Yes

### Electrical Characteristics

#### Electricals

Max. Conductor DCR	Max. DCR Unbalance	Max. Capacitance Unbalance	Nom. Mutual Capacitance
77 Ohm/km	3%	90 pF/100m	15.5 pF/ft

#### Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Typical Delay Skew
100 MHz	537.6 ns/100m	35 ns/100m	30 ns/100m

#### High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance
1 MHz	2.0 dB/100m	84.3 dB	82.3 dB	80.3 dB	80.3 dB	76.8 dB	73.8 dB	20.0 dB	100 ± 15	
4 MHz	3.7 dB/100m	75.3 dB	73.3 dB	69.5 dB	69.5 dB	64.8 dB	61.8 dB	23.6 dB	100 ± 15	100 ± 12 Ohm
8 MHz	5.3 dB/100m	70.8 dB	68.8 dB	63.5 dB	63.5 dB	58.7 dB	55.7 dB	25.3 dB	100 ± 15	100 ± 10.4 Ohm
10 MHz	5.9 dB/100m	69.3 dB	67.3 dB	61.4 dB	61.4 dB	56.8 dB	53.8 dB	26.0 dB	100 ± 15	100 ± 8 Ohm
16 MHz	7.4 dB/100m	66.2 dB	64.2 dB	56.8 dB	56.8 dB	52.7 dB	49.7 dB	26.0 dB	100 ± 15	100 ± 7.3 Ohm
20 MHz	8.3 dB/100m	64.8 dB	62.8 dB	54.4 dB	54.4 dB	50.8 dB	47.8 dB	26.0 dB	100 ± 15	100 ± 5.7 Ohm
25 MHz	9.4 dB/100m	63.3 dB	61.3 dB	52.0 dB	52.0 dB	48.8 dB	45.8 dB	25.5 dB	100 ± 15	100 ± 5 Ohm
31.25 MHz	10.5 dB/100m	61.9 dB	59.9 dB	49.4 dB	49.4 dB	46.9 dB	43.9 dB	25.0 dB	100 ± 15	100 ± 5 Ohm
62.5 MHz	15.1 dB/100m	57.4 dB	55.4 dB	40.3 dB	40.3 dB	40.9 dB	37.9 dB	23.5 dB	100 ± 15	100 ± 5 Ohm

100 MHz	19.3 dB/100m	54.3 dB	52.3 dB	33.0 dB	33.0 dB	36.8 dB	33.8 dB	22.5 dB	100 ± 15	100 ± 5 Ohm
155 MHz	24.5 dB/100m	51.4 dB	49.4 dB	24.9 dB	24.9 dB	33.0 dB	30.0 dB	21.6 dB	100 ± 22	100 ± 5 Ohm
200 MHz	28.2 dB/100m	49.8 dB	47.8 dB	19.6 dB	19.6 dB	30.8 dB	27.8 dB	21.0 dB	100 ± 22	100 ± 5 Ohm
250 MHz	31.8 dB/100m	48.3 dB	46.3 dB	14.5 dB	14.5 dB	28.8 dB	25.8 dB	20.5 dB	100 ± 32	100 ± 5 Ohm
300 MHz	35.2 dB/100m	47.1 dB	45.1 dB	9.9 dB	9.9 dB	27.3 dB	24.3 dB	20.1 dB	100 ± 32	100 ± 5 Ohm
350 MHz	38.4 dB/100m	46.1 dB	44.1 dB	5.7 dB	5.7 dB	25.9 dB	22.9 dB	19.8 dB	100 ± 32	100 ± 5 Ohm
400 MHz	41.5 dB/100m	45.3 dB	43.3 dB	1.8 dB	1.8 dB	24.8 dB	21.8 dB	19.5 dB	100 ± 32	100 ± 5 Ohm
450 MHz	44.3 dB/100m	44.5 dB	42.5 dB			23.7 dB	20.7 dB	19.2 dB	100 ± 32	100 ± 5 Ohm
500 MHz	47.1 dB/100m	43.8 dB	41.8 dB			22.8 dB	19.8 dB	19.0 dB	100 ± 32	100 ± 5 Ohm
550 MHz	49.7 dB/100m	43.2 dB	41.2 dB			22.0 dB	19.0 dB	18.8 dB	100 ± 32	100 ± 5 Ohm
600 MHz	52.3 dB/100m	42.6 dB	40.6 dB			21.2 dB	18.2 dB	18.7 dB	100 ± 32	100 ± 5 Ohm
650 MHz	54.8 dB/100m	42.1 dB	40.1 dB			20.5 dB	17.5 dB	18.5 dB	100 ± 32	100 ± 5 Ohm

#### Voltage

<b>UL Voltage Rating</b>
300 V (CMP), 300 V (CL3P)

### Mechanical Characteristics

#### Temperature

UL Rating	Operating	Installation	Storage
105°C	-20°C To +75°C	0°C To +50°C	-20°C To +75°C

#### Bend Radius

Stationary Min.	Installation Min.
0.5 in	2.5 in

Max. Pull Tension:	40 lbs
Bulk Cable Weight:	31 lbs/1000ft

### Standards and Compliance

Environmental Suitability:	Plenum, Indoor
Sustainability:	Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Fire Resistance:	NFPA 262, UL 910 (Plenum), FT6, FT6, IEC 60332-1-2
NEC / UL Compliance:	800, CMP;CMP-LP (0.6A);CL3P-LP (0.6A)
CEC / C(UL) Compliance:	CMP
ICEA Compliance:	S-116-732-2013
IEEE Compliance:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
NEMA Compliance:	ANSI/NEMA WC-66
Data Category:	Category 6
TIA/EIA Compliance:	ANSI/TIA-568.2-D Category 6
Cenelec Compliance:	Segregation class according EN50174-2=a
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16
APAC Compliance:	China RoHS II (GB/T 26572-2011)

### Part Number

Non-Plenum Number:	3632
--------------------	------

#### Variants

Item #	Color	Putup Type	Length	UPC
3633 0101000	Black	Reel	1,000 ft	612825146421
3633 010A1000	Black	Reel-in-Box	1,000 ft	612825146414
3633 D151000	Blue	Reel	1,000 ft	612825146261
3633 D15A1000	Blue	Reel-in-Box	1,000 ft	612825146247
3633 D15U1000	Blue	UnReel	1,000 ft	612825146254
3633 0081000	Gray	Reel	1,000 ft	612825146377
3633 008A1000	Gray	Reel-in-Box	1,000 ft	612825146353
3633 008U1000	Gray	UnReel	1,000 ft	612825146360
3633 0051000	Green	Reel	1,000 ft	612825146346

3633 005A1000	Green	Reel-in-Box	1,000 ft	612825146339
3633 0031000	Orange	Reel	1,000 ft	612825146308
3633 003A1000	Orange	Reel-in-Box	1,000 ft	612825146292
3633 0021000	Red	Reel	1,000 ft	612825146285
3633 002A1000	Red	Reel-in-Box	1,000 ft	612825146278
3633 0091000	White	Reel	1,000 ft	612825146407
3633 009A1000	White	Reel-in-Box	1,000 ft	612825146384
3633 009U1000	White	UnReel	1,000 ft	612825146391
3633 0041000	Yellow	Reel	1,000 ft	612825146322
3633 004A1000	Yellow	Reel-in-Box	1,000 ft	612825146315

## Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Values above 400 MHz are for Engineering Information Only. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0.
--------	--

## History

Update and Revision:	Revision Number: 0.406 Revision Date: 07-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Multi-Conductor Cables](#) category:*

*Click to view products by [Belden](#) manufacturer:*

Other Similar products are found below :

[89182-010-1000](#) [89705-008-500](#) [89842-002-1000](#) [6000FE-877-1000](#) [6120UL-002-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6300FE-877-U1000](#) [6309UE-877-1000](#) [M3905-BK005](#) [6502FE 8771000](#) [6541PA-008-U1000](#) [CV6807-000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#) [82841-877-5000](#) [83318E-009-500](#) [8348-060-500](#) [83559-002-1000](#) [83653-002-5000](#) [83659-002-1000](#) [83709-002-1000](#) [8404-060-500](#) [8469 060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-060-U1000](#) [8747-060-100](#) [8747-060-1000](#) [8769-060-1000](#) [8775-060-500](#) [8780-060-1000](#) [8782-001-U1000](#) [88444-002-1000](#) [9159-060-500](#) [9318-060-1000](#) [939870-000](#) [9423 060U500](#)