

Product: <u>39116</u> ⊠	
Lead Wire, #16 Str TC, PPO Ins, AWM 11	028
😭 Request Sample	

Product Description

Low Temp Plastic Lead Wire, 16AWG (26x30) Tinned Copper, PPO Insulation, AWM 11028 600V 105C VW-1

Technical Specifications

Product Overview

Suitable Applications:	Electrical panel builders, Electrical/electronic manufacturers, Appliance manufacturers, Furniture, Computer manufacturers, Automotive companies and their sub-suppliers

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
16	26x30	TC - Tinned Copper	1
Condu	ctor Count:		1

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PPO - Polyphenylene Oxide	0.083 in	0.012 in

Electrical Characteristics

Conductor DCR			
Nominal Conductor DC			

4.0 Ohm/1000ft

Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	Single conductor in free air @ 30°C: 26 A

Voltage

UL Voltage Rating 600 V RMS

Temperature Range

UL Temp Rating:	105°C		
Operating Temp Range:	-40°C To +105°C Dry		
Mechanical Characteristics			
Bulk Cable Weight:	10 lbs/1000ft		
Standards			
UL AWM Style Compliance:	UL AWM Style 11028		
Applicable Environmental and Other Programs			
EU Directive 2000/53/EC (ELV):	Yes		

EU Directive 2003/96/EC (BFR):	Yes			
EU Directive 2011/65/EU (ROHS II):	Yes			
EU Directive 2012/19/EU (WEEE):	Yes			
EU Directive 2015/863/EU:	Yes			
EU Directive Compliance:	Directive 2003/11/EC (BFR)			
EU CE Mark:	Yes			
EU RoHS Compliance Date (yyyy-mm-dd):	2011-04-01			
CA Prop 65:	Yes			
CA FIOP 05.	165			

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum	(Y/N):		

Part Number

Variants

ltem #	Color	Putup Type	Length	UPC
39116 010100	Black	Reel	100 ft	612825149118
39116 0101000	Black	Reel	1,000 ft	612825149125
39116 0105000	Black	Reel	5,000 ft	612825149132
39116 013100	Blue, Dark	Reel	100 ft	612825149149
39116 0131000	Blue, Dark	Reel	1,000 ft	612825149156
39116 0135000	Blue, Dark	Reel	5,000 ft	612825149163
39116 001100	Brown	Reel	100 ft	612825148876
39116 0011000	Brown	Reel	1,000 ft	612825148883
39116 0015000	Brown	Reel	5,000 ft	612825148890
39116 008100	Gray	Reel	100 ft	612825149057
39116 0081000	Gray	Reel	1,000 ft	612825149064
39116 0085000	Gray	Reel	5,000 ft	612825149071
39116 005100	Green, Dark	Reel	100 ft	612825148999
39116 0055000	Green, Dark	Reel	5,000 ft	612825149019
39116 189100	Green, Yellow Stripe	Reel	100 ft	612825149170
39116 1891000	Green, Yellow Stripe	Reel	1,000 ft	612825149187
39116 1895000	Green, Yellow Stripe	Reel	5,000 ft	612825149194
39116 003100	Orange	Reel	100 ft	612825148937
39116 0035000	Orange	Reel	5,000 ft	612825148951
39116 002100	Red	Reel	100 ft	612825148906
39116 0021000	Red	Reel	1,000 ft	612825148913
39116 0025000	Red	Reel	5,000 ft	612825148920
39116 0075000	Violet	Reel	5,000 ft	612825149040
39116 009100	White	Reel	100 ft	612825149088
39116 0091000	White	Reel	1,000 ft	612825149095
39116 0095000	White	Reel	5,000 ft	612825149101
39116 004100	Yellow	Reel	100 ft	612825148968
39116 0041000	Yellow	Reel	1,000 ft	612825148975
33110 0041000				
39116 0045000	Yellow	Reel	5,000 ft	612825148982
	Yellow	Reel C - CRAT		

No

Product Notes

Notes:	Halogen-free.			
History				
Update and Revision:	Revision Number: 0.312 Revision Date: 07-26-2020			

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000 BFWUL3239-24-PINK 22759/34-16-9CS2621 22759/42-24-9CS2620 933205-000 284711-000 961473-000 30802-009-250 30808-010-500 30810-010-500 99M0111-20-2 A00594-000 190571-000 22759/41-12-9CS2620 22759/41-16-9CS2620 22759/43-10-9CS2873 265925-000 CM9524-000 CMC-0553-1-9 31510-010-250 31514-009-500 32412-009-500 34401-010-250 34402-010-500 M81044/9-4-9 391441-BK007 400R0111-10-9 431660-000 ATFC0311-20-0 ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-99 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0211-20-5CS2502 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278