



Product Description

Security & Sound Cable, Riser-CMR, 4-16 AWG stranded bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Product Overview			
Suitable Applications:	Security System, Intercom/PA, Audio/Speaker	, Power-Limited Controls	
Construction Details			
Conductor			
Element Number of Elemen			
Conductor(s) 4	16 AWG 19x29 BC - Bare Copper		
Insulation			
Element Material	Nom. Thickness Color Code		
Conductor(s) PP - Polypropylene	0.008 in (0.20 mm) Black, Red, White, Green		
Outer Jacket			
Material Nom. T	hickness Nom. Diameter Ripcord		
PVC - Polyvinyl Chloride 0.017 in	(0.43 mm) 0.210 in (5.33 mm) Yes		
Overall Cable Diameter (Nominal):	0.210 in (5.33 mm)		
Electrical Characteristics			
Electrical Characteristics			
	r DCR Nom. Capacitance Cond-to-Cond	Max. Current	
Electricals		Max. Current 5.0 Amps per conductor @ 25°C	
Electricals Element Nom. Conducto			
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14			
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage			
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR)	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR)	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristic	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristi Temperature	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conducto Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristi Temperature UL Temperature Operating	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conducto Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristi Temperature UL Temperature Operating 75°C -20°C to +75°C Bend Radius	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristi Temperature UL Temperature Operating 75°C -20°C to +75°C Bend Radius	Ohm/km) 23 pF/ft (75 pF/m)		
Electricals Element Nom. Conductor Conductor(s) 4.2 Ohm/1000ft (14 Voltage UL Voltage Rating 300 V (CMR) Mechanical Characteristi Temperature UL Temperature UL Temperature Stationary Min. Installation Min	Ohm/km) 23 pF/ft (75 pF/m)		

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL1666 Riser, FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6202UE

History

Update and Revision:

Revision Number: 0.284 Revision Date: 12-15-2021

Variants

Item #	Color	Putup Type	Length	UPC/EAN
5202UE 010500	Black			612825157960
5202UE 010U1000	Black			612825157953
5202UE 0081000	Gray			612825157922
5202UE 008500	Gray			612825157939
5202UE 008U1000	Gray			612825336587
5202UE 008U500	Gray			612825157915
5202UE.00152	Gray	Reel	152 m	8719605008107
5202UE.00305	Gray	Reel	305 m	8719605008114
5202UE.00U305	Gray	Reel	305 m	8719605008121
5202UE 009U1000	White			612825157946

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927-000 01342.35T.01 01364.35T.01 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 706/2R-BLACK-EACH 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164-CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006-DK-GRN-100 83008-WHT-1000 83009-BLK-100