



Product: <u>5320UL</u> ☑

Fire Alarm, #18-2c BC, FPLR

Product Description

Fire Alarm Cable, Riser-FPLR, 2-18 AWG solid bare copper conductors with polypropylene insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Conductor(s)	2	18 AWG	Solid	BC - Bare Copper

Insulation

Element	Material	Nom. Thickness	Color Code
Conductor(s)	PP - Polypropylene	0.007 in (0.18 mm)	Black, Red

Outer Jacket

	Material	Nom. Thickness	Nom. Diameter	Ripcord
	PP - Polypropylene	0.017 in (0.43 mm)	0.143 in (3.63 mm)	Yes
ĺ	Overall Cable Diame	eter (Nominal): 0.14	3 in (3.63 mm)	

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield	Max. Current
Conductor(s)	6.4 Ohm/1000ft (21 Ohm/km)	29 pF/ft (95 pF/m)	29 pF/ft (95 pF/m)	5 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V (FPLR)

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	-20°C to +75°C

Bend Radius

Stationary Min.	Installation Min.
in (00)	4.4 in (00 mm)
1.4 in (36 mm)	1.4 in (36 mm)
Max. Pull Tension	n:
Bulk Cable Weigh	ht:

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL1666 Riser, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 760, FPLR
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6320UL

History

Update and Revision:	Revision Number: 0.280 Revision Date: 12-15-2021

Variants

Item #	Color	UPC
5320UL 0101000	Black	612825160526
5320UL 010U1000	Black	612825160519
5320UL D151000	Blue	612825160465
5320UL D15C500	Blue	612825160458
5320UL 001U1000	Brown	612825160472
5320UL 0021000	Red	612825160502
5320UL 002C500	Red	
5320UL 002U1000	Red	612825160489
5320UL 002U500	Red	612825160496
5320UL 009C500	White	

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

01342.35T.01 01364.35T.01 CS2885-000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 644833-000 6500FE-877-1000 CW9530-000 CX6543000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CY0660-000 730859-000 MCC-USB-4-250 768146-000 773159-000 820457-000
82907-NAT-500 83005-WHT-500 83023-YEL-500 83027-RED-100 83029-GRN-100 8302-CHR-500 83046-RED-100 8305-CHR-100
83333-WHT-100 8334-060-1000 83652-RED-100 8404-060-500 8434-CHR-100 8441-BLK-1000 8450-BLK-1000 8451-GRY-U500 8459CHR-500 8465-CHR-1000 8466-CHR-1000 8467-CHR-1000 8469 060100 8469-CHR-1000 8471-CHR-1000 8472-BLK-250 8473-CHRU500 8501-ORG-100 8501-RED-100 8502-GRY-100 8503-WHT/BLU-100 8520-BRN-100 8520-GRY-100 8523-GRY-100 8523-GRY-