

# **Product:** <u>5340F1</u> ⊠ Security & Sound, #18-2c, TC, Shielded, CMG-FPL-PLTC-ER, Water-Blocked

## **Product Description**

Security & Sound Cable, Rated-CMG-FPL-PLTC-ER, 1-18 AWG stranded tinned copper pair with PVC insulation, Beldfoil® shield, Waterblocking tape, PVC jacket

## **Technical Specifications**

#### **Product Overview**

Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy & Wet Location, Below-Gr         Construction Details         Conductor         Element       Number of Element       AWG       Stranding       Material         Pair(s)       1       18       7x26       TC - Tinned Copper         nsulation       Element       Material       Thickness [in]       Color Code         Pair(s)       PVC - Polyvinyl Chloride       0.010       Black & Red         Duter Shield Material         Shield Type       Material       Coverage       Drainwire Type         Tape       Bi-Laminate (Alum+Poly)       100%       20 AWG (7x28) TC         Vater Jacket Material         Material       Nom. Diameter         PVC - Polyvinyl Chloride       0.037 in       0.232 in	Constru Conducto			rity System, I	ntercom/PA, Audio/Sp	beaker Pov	wer-Limited	Controle N	loisy & We		
Sonductor         Element       Number of Element       AWG       Stranding       Material         Pair(s)       1       18       7x26       TC - Tinned Copper         nsulation       Element       Material       Thickness [in.]       Color Code         Pair(s)       PVC - Polyvinyl Chloride       0.010       Black & Red         Outer Shield Material       Coverage       Drainwire Type         Tape       Bi-Laminate (Alum+Poly)       100%       20 AWG (7x28) TC         Waterblock Ing:       Waterblock Tape       Vaterblock Tape         Duter Jacket Material       Thickness       Nom. Diameter         PVC - Polyvinyl Chloride       0.037 in       0.232 in	Conducto	uction Details				Jourior, For	WCI-LINICO	Controls, I		Location, E	elow-G
Element     Number of Element     AWG     Stranding     Material       Pair(s)     1     18     7x26     TC - Tinned Copper       nsulation     Element     Material     Thickness [in.]     Color Code       Pair(s)     PVC - Polyvinyl Choride     0.010     Black & Red       Outer Shield Material     Coverage     Drainwire Type       Tape     Bi-Laminate (Alum+Poly)     100%     20 AWG (7x28) TC       Waterblock Irage     Waterblock Tape											
Element       Number of Element       AWG       Stranding       Material         Pair(s)       1       18       7x26       TC - Tinned Copper         nsulation       Element       Material       Thickness [in.]       Color Code         Pair(s)       PVC - Polyvinyl Chloride       0.010       Black & Red         Outer Shield Type       Material       Coverage       Drainwire Type         Tape       Bi-Laminate (Alum+ Poly)       100%       20 AWG (7x28) TC         Waterblocking:       Waterblock Tape       Vaterblock Tape         Duter Jacket Material       Thickness       Nom. Diameter         PVC - Polyvinyl Chloride       0.037 in       0.232 in											
Pair(s)       1       18       7x26       TC - Tinned Copper         nsulation       Element       Material       TH Kness [in.]       Color Code         Pair(s)       PVC - Polyvinyl Chloride       0.010       Black & Red         Duter Shield Type       Material       Coverage       Drainwire Type         Tape       Bi-Laminate (Alum+Poly)       100%       20 AWG (7x28) TC         Waterblocking:       Waterblock Tape         Duter Jacket Material       Thickness       Nom. Diameter         PVC - Polyvinyl Chloride       0.037 in       0.232 in		r									
Insulation          Element       Material       Thickness [in.]       Color Code         Pair(s)       PVC - Polyvinyl Chloride       0.010       Black & Red         Duter Shield Type       Material       Coverage       Drainwire Type         Tape       Bi-Laminate (Alum+Poly)       100%       20 AWG (7x28) TC         Waterblocking:       Waterblock Tape         Duter Jacket Material       Thickness       Nom. Diameter         PVC - Polyvinyl Chloride       0.037 in       0.232 in	Element	Number of Elem	ent AWG	Stranding	Material						
Element     Material     Thickness [in.]     Color Code       Pair(s)     PVC - Polyvinyl Chloride     0.01     Black & Red         Duter Shield Type     Material     Coverage     Drainwire Type       Tape     Bi-Laminate (Alum+Poly)     100%     20 AWG (7x28) TC       Waterblocking:     Waterblock Tape   Duter Jack taterial       Material     Thickness     Nom. Diameter       PVC - Polyvinyl Chloride     0.037 in     0.232 in	Pair(s)	1	18	7x26	TC - Tinned Copper						
Pair(s)     PVC - Polyvinyl Chloride     0.010     Black & Red       Duter Shield Type     Material     Coverage     Drainwire Type       Shield Type     Bi-Laminate (Alum+Poly)     100%     20 AWG (7x28) TC       Waterblocking:     Waterblock Tape       Duter Jack E Material     Thickness     Nom. Diameter       PVC - Polyvinyl Chloride     0.037 in     0.232 in	nsulation										
Material     Coverage     Drainwire Type       Tape     Bi-Laminate (Alum+Poly)     100%     20 AWG (7x28) TC       Waterblocking:     Waterblock Tape         Duter Jacket Material     Thickness     Nom. Diameter       PVC - Polyvinyl Chloride     0.037 in     0.232 in	Element	Material	Th	ickness [in.]	Color Code						
Shield Type     Material     Coverage     Drainwire Type       Tape     Bi-Laminate (Alum+Poly)     100%     20 AWG (7x28) TC       Waterblocking:     Waterblock Tape         Duter Jacket Material     Thickness     Nom. Diameter       PVC - Polyviry I Chloride     0.037 in     0.232 in	Pair(s)	PVC - Polyvinyl C	hloride 0.0	010	Black & Red						
Waterblocking:     Waterblock Tape       Duter Jacket Material     Thickness     Nom. Diameter       PVC - Polyvinyl Chloride     0.037 in     0.232 in			rial	Coverage	Drainwire Type						
Material     Thickness     Nom. Diameter       PVC - Polyvinyl Chloride     0.037 in     0.232 in	Tape	Bi-Laminate (	Alum+Poly	) 100%	20 AWG (7x28) TC						
MaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.037 in0.232 in	Waterbloo	cking:	Wate	rblock Tape		-					
MaterialThicknessNom. DiameterPVC - Polyvinyl Chloride0.037 in0.232 in	Jutor lac	kot Matorial									
PVC - Polyvinyl Chloride 0.037 in 0.232 in			nickness	Nom Diame	ter						
Cable Diameter (Nominal): 0.232 in											
	Cable Dia	ameter (Nominal)	0 232	? in							
	04010 010		0.202								
	lectricals	5									

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond
Pair(s)	5.9 Ohm/1000ft	65 pF/ft
Nom Outer Shield DCR:		16.9 Ohm/1000ft

#### Voltage

UL Voltage Rating 300 V (CMG, FPL, PLTC-ER)

#### **Mechanical Characteristics**

#### Temperature

 UL Rating
 Operating

 105°C
 -30°C to +105°C

Bend Radius

Stationary Min.	Installation Mi	in.
2.5 in	2.3 in	
Max. Pull Tensio	n:	57
Bulk Cable Weig	ht:	27

#### **Standards and Compliance**

Environmental Suitability:	Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Burial
Flammability / Fire Resistance:	UL1685 (FT4 Loading), FT4, 1202, IEC 60332-1-2
NEC / UL Compliance:	Article 725, Article 760, Article 800, CMG, FPL, PLTC-ER
CEC / C(UL) Compliance:	CMG
CPR Euroclass:	Eca
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### **History**

Update and Revision: Revision Number: 0.265 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 89705-008-500
 6000FE-877-1000
 CS2885-000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 M3905-BK005

 6502FE
 8771000
 6541PA-008-U1000
 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA 

 0078-22-4-9CS2405
 CXA-0078-24-4-9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 768146-000
 773159-000

 82841-877-5000
 83318E-009-500
 8348-060-500
 83559-002-1000
 83653-002-5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469

 060100
 858171-000
 8628-060-500
 868361-001
 8730-060-1000
 8737-060-U1000
 8747-060-100
 8769-060-1000
 8775-060 

 500
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 939870-000
 9423
 060U500
 9444
 060U1000
 9497

 0001000
 877541-000
 8782-001-U1000
 88444-002-1000
 9159-060-500
 939870-000
 9423
 060U500
 9444
 060U1000
 9497