

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

**Picture
Not Available**

For more Information
please call

1-800-Belden1



General Description:

Access Control Cable, Riser-CMR, 4-18 AWG conductors, 6-22 AWG conductors with Beldfoil® shield, 4-22 AWG conductors, 4-22 AWG conductors, All conductors stranded bare copper with FR-PVC insulation, Each cable has PVC jacket, Banana Peel® No overall jacket

Usage (Overall)

Suitable Applications: Access Control

Twisted Pair

Physical Characteristics
Individual Shield

Multi Conductor

Physical Characteristics
Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
4	22	7x30	BC - Bare Copper	0.029
4	22	7x30	BC - Bare Copper	0.029
6	22	7x30	BC - Bare Copper	0.029
4	18	7x26	BC - Bare Copper	0.046

Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)	Dia. (in.)	AWG
PVC - Polyvinyl Chloride	0.010	0.049	22
PVC - Polyvinyl Chloride	0.010	0.066	18

Insulation Color Code Chart:

Number	Color	Description
1	Black	Door Contact 1
2	Red	Door Contact 2
3	White	Door Contact 3
4	Green	Door Contact 4
5	Black	Rex/Spare 1
6	Red	Rex/Spare 2
7	White	Rex/Spare 3
8	Green	Rex/Spare 4
9	Black	Lock/Power 1
10	Red	Lock/Power 2
11	White	Lock/Power 3
12	Green	Lock/Power 4
13	Black	Card Reader 1
14	Red	Card Reader 2
15	White	Card Reader 3
16	Green	Card Reader 4
17	Yellow	Card Reader 5
18	Orange	Card Reader 6

Individual Shield

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)	Description
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000	Card Reader

Outer Shield Drain Wire AWG:

Component	AWG	Stranding	Drain Wire Conductor Material
Card Reader	24	7X32	TC - Tinned Copper

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC	0.020

Outer Jacket Diameter:

Component #	Nom. Dia. (in.)
Door Contact	0.158
Rex/Spare	0.158
Reader	0.189
Lock/Power Card	0.198

Outer Jacket Ripcord: Yes

Outer Jacket Color Code Chart:

Number	Color	Description
1	White	Door Contact
2	Blue	Rex/Spare
3	Orange	Card Reader
4	Gray	Lock/Power

Mechanical Characteristics

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75C

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

NEC Articles: 800

CEC/C(UL) Specification: CMG

Flame Test

UL Flame Test: UL1666 Vertical Shaft

Suitability

Suitability - Indoor: Yes

Electrical Characteristics

Nom. Capacitance Conductor to Shield:

Description	Freq. (MHz)	Capacitance (pF/ft)
Card Reader	0.001	56.000

Nom. Capacitance Conductor to Conductor:

Description	Freq. (MHz)	Capacitance (pF/ft)
Door Contact	0.001	24.000
Rex/Spare	0.001	24.000
Card Reader	0.001	31.000
Lock Power	0.001	29.000

Nom. Conductor DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Door Contact	16.100
Rex/Spare	16.100
Card Reader	16.300
Lock Power	6.500

Nominal Outer Shield DC Resistance:

Description	DCR @ 20°C (Ohm/1000 ft)
Card Reader	13.900

Max. Operating Voltage - UL:

Voltage	Description
300V	UL type CMR

Max. Recommended Current:

Description	Current
Door Contact	2.8 Amps @ 25C ambient (10C temperature rise)
Rex/Spare	2.8 Amps @ 25C ambient (10C temperature rise)
Card Reader	2.0 Amps @ 25C ambient (10C temperature rise)
Lock Power	4.0 Amps @ 25C ambient (10C temperature rise)

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Physical Characteristics (Overall)

Conductor

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
Unjacketed

Overall Cable

Overall Nominal Diameter: 0.425 in.

Mechanical Characteristics (Overall)

Bulk Cable Weight: 94 lbs/1000 ft.

Max. Recommended Pulling Tension: 217 lbs.

Min. Bend Radius/Minor Axis: 4.250 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMR

NEC Articles: 800

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Applicable Patents:

Country
www.belden.com/p

Flame Test

UL Flame Test: UL1666 Vertical Shaft

C(UL) Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Plenum Number: 658GMS

Notes (Overall)

Notes: Cold environment installation: When installing cables that have been stored at ambient temperatures of 32 degrees Fahrenheit (0 degrees Centigrade) or lower, Belden recommends conditioning of the cable for 12 hours at room temperature prior to individual cable leg separation.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
558GMS 0001000	1,000 FT	103.000 LB	NONE	C	4C22+4C22+6C22FS+4C18 CMR BP

Notes:

C = CRATE REEL PUT-UP.

558GMS Composite - Lock Power, Card Reader, Door Contact, REX Applications

Revision Number: 1 Revision Date: 01-24-2017

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Conductor Cables](#) category:

Click to view products by [Belden](#) manufacturer:

Other Similar products are found below :

[89182-010-1000](#) [89705-008-500](#) [6000FE-877-1000](#) [CS2885-000](#) [M27500-20SP2S23](#) [6300FE-877-U1000](#) [6309UE-877-1000](#) [M3905-BK005](#)
[6502FE 8771000](#) [6541PA-008-U1000](#) [CV6807-000](#) [CW9530-000](#) [CX6543-000](#) [CXA-0066-20-4-9CS2973](#) [CXA-0078-16-1-9CS2405](#) [CXA-](#)
[0078-22-4-9CS2405](#) [CXA-0078-24-4-9CS2405](#) [CXA-0140-16-6/9-9CS2405](#) [CY0660-000](#) [720451-000](#) [752687-000](#) [768146-000](#) [773159-000](#)
[82841-877-5000](#) [83318E-009-500](#) [8348-060-500](#) [83559-002-1000](#) [83653-002-5000](#) [83659-002-1000](#) [83709-002-1000](#) [8404-060-500](#) [8469](#)
[060100](#) [858171-000](#) [8628-060-500](#) [868361-001](#) [8730-060-1000](#) [8737-060-U1000](#) [8747-060-100](#) [8747-060-1000](#) [8769-060-1000](#) [8775-060-](#)
[500](#) [8780-060-1000](#) [8782-001-U1000](#) [88444-002-1000](#) [9159-060-500](#) [939870-000](#) [9423 060U500](#) [9444 060U1000](#) [9497 0001000](#) [9515-060-](#)
[1000](#)