

Product: <u>6301UE</u> ☑

Security & Sound, 3 Conductor 18 AWG BC, CMP



Product Description

Security & Commercial Audio Cable, 3 Conductor 18 AWG stranded (7x26) bare copper conductors with Flamarrest® insulation, Plenum-CMP, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems

Construction Details

Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	3	18	7x26	BC - Bare Copper
Insulation				

Element	Material	Thickness [in.]	Color Code
Conductor(s)	PVC-LS - Polyvinyl Chloride (Low Smoke)	0.009	Black, Red, White

Outer Jacket Material

	Material		Thickness	Nom. Diameter	Ripcord
F	PVC-LS - Polyvinyl Chloride (Low Smoke)		0.015 in	0.163 in	Yes
(Cable Diameter (Nominal):				

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	6.5 Ohm/1000ft	34 pF/ft	5 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V (CMP)

Mechanical Characteristics

Temperature

UL Rating	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min.	Installation Mi	in.
1.625 in	1.6 in	
Max. Pull Tensio	n:	67
Bulk Cable Weig	ht:	23

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Fire Resistance:	NFPA 262, UL 910 (Plenum), FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	СМР
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5301UE
History	

Update and Revision:	Revision Number: 0.308 Revision Date: 07-31-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

 89182-010-1000
 6000FE-877-1000
 M27500-20SP2S23
 6300FE-877-U1000
 6309UE-877-1000
 6502FE 8771000
 6541PA-008-U1000

 CV6807-000
 CW9530-000
 CX6543-000
 CXA-0066-20-4-9CS2973
 CXA-0078-16-1-9CS2405
 CXA-0078-22-4-9CS2405
 CXA-0078-24-4

 9CS2405
 CXA-0140-16-6/9-9CS2405
 CY0660-000
 720451-000
 752687-000
 82841-877-5000
 8348-060-500
 83559-002-1000
 83653-002

 5000
 83659-002-1000
 83709-002-1000
 8404-060-500
 8469
 060100
 8628-060-500
 868361-001
 8730-060-1000
 8747-060

 100
 8747-060-1000
 8769-060-1000
 8775-060-500
 877541-000
 8780-060-1000
 88444-002-1000
 9159-060-500
 939870-000
 9423
 060U500

 9444
 060U1000
 9497
 0001000
 9515-060-1000
 9524-060-1000
 9546-060-500
 9572-002-U500
 9774-060-1000
 1213F-D15

 A1000
 1213F-009-A1000
 1213F-009-A1000
 1213F-D15 1213F-D15 1213F-D15