



Product Description

Fire Alarm Cable, Plenum-FPLP, 2-18 AWG solid bare copper conductors with FEP insulation, Flamarrest® jacket with ripcord

Technical Specifications

Suitable Applications:		1	Fire Alarm, Addressable Systems, Circuits: Audio, Control, Initiating, Notification							
Constructi	ion Deta	ils								
Conductor										
Element	Number	of Element	Size	Strand	ing	Material				
Conductor(s)	2		18 AWG	Solid	BC	C - Bare Co	oper			
nsulation										
Element		Materi	rial		Nom. Thickness Nor		Nom	. Insulation I	Diameter	Color Code
Conductor(s)	FEP - Flu	orinated Eth	ylene Prop	pylene (0.007 in	(0.18 mm)	0.05	4 in (1.4 mm)		Black, Red
Outer Jacket Mater	ial	Nom. Thi	ckness	Nom. Di	iameter	Ripcord				
Outer Jacket										
Mater	ial	Nom. Thi	ckness	Nom. Di	iameter	Ripcord				
PVC - Polyvin										
	yl Chloride	0.015 in (0).38 mm)	0.138 in		Yes				
Overall Cable				0.138 in		Yes				
Overall Cable	Diameter ((Nominal):		0.138 in		Yes				
Overall Cable	Diameter ((Nominal):		0.138 in		Yes				
Overall Cable	Diameter ((Nominal):		0.138 in		Yes				
Overall Cable Electrical	Diameter ((Nominal):	0.138 in				c. Cur	rent		
Overall Cable	Diameter (Character ctor DCR	(Nominal): (0.138 in		Cond	Ma		rent uctor at 25°C		
Overall Cable Electrical Electricals Nom. Conduc 6.78 Ohm/100	Diameter (Character ctor DCR	(Nominal): (eristics Nom. Capa	0.138 in		Cond	Ma				
Overall Cable Electrical Electricals Nom. Condu 6.78 Ohm/100 Voltage	Diameter (Character ctor DCR DOft	(Nominal): (eristics Nom. Capa	0.138 in		Cond	Ma				
Overall Cable Electrical (Electricals Nom. Conduc 6.78 Ohm/100 Voltage UL Voltage R	Diameter (Character ctor DCR DOft	(Nominal): (eristics Nom. Capa	0.138 in		Cond	Ma				
Overall Cable Electrical Electricals Nom. Condu 6.78 Ohm/100 Voltage	Diameter (Character ctor DCR DOft	(Nominal): (eristics Nom. Capa	0.138 in		Cond	Ma				
Overall Cable Electrical (Electricals Nom. Conduc 6.78 Ohm/100 Voltage UL Voltage R	Diameter (Character ctor DCR D0ft	Nominal): (eristics Nom. Capa 26 pF/ft (85	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical (Electricals Nom. Condu 6.78 Ohm/100 Voltage UL Voltage R 300 V	Diameter (Character ctor DCR D0ft	Nominal): (eristics Nom. Capa 26 pF/ft (85	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical (Electricals Nom. Conduc 6.78 Ohm/100 Voltage UL Voltage R 300 V Mechanica	Diameter (Character ctor DCR D0ft	Nominal): (eristics Nom. Capa 26 pF/ft (85	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical Commentation Electricals Nom. Conduct 6.78 Ohm/100 Coltage UL Voltage R 300 V Mechanica Femperature	Diameter (Charactic ctor DCR DOft tating	Nominal): (eristics Nom. Capa 26 pF/ft (85	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical Commentation Electricals Nom. Conduct 6.78 Ohm/100 Coltage UL Voltage R 300 V Mechanica Femperature	Diameter (Charactic ctor DCR DOft tating	(Nominal): (eristics Nom. Capa 26 pF/ft (85 cteristics	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical Cable Electrical Nom. Condu C	Diameter (Charactic ctor DCR DOft tating	(Nominal): (eristics Nom. Capa 26 pF/ft (85 cteristics	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical Cable Electrical Nom. Condu C	Diameter (Character ctor DCR DOft tating	(Nominal): (eristics Nom. Capa 26 pF/ft (85 cteristics	D. 138 in Incitance C IpF/m)		Cond	Ma				
Overall Cable Electrical (Electricals Nom. Condu 6.78 Ohm/100 Voltage UL Voltage R 300 V Mechanica Temperature UL Temperature 75°C Bend Radius	Diameter (Character ctor DCR Doft tating al Chara ure Ope 0°C T	(Nominal): (eristics Nom. Capa 26 pF/ft (85 Cteristics cteristics rating o +75°C	D. 138 in Incitance C IpF/m)		Cond	Ma				

Bulk Cable Weight:	15 lbs/1000ft
--------------------	---------------

Standards and Compliance

Indoor
NFPA 262 (UL910)
Article 760, FPLP
EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
China RoHS II (GB/T 26572-2011)
California State Fire Marshall
5320UJ

Teflon® is a trademark of DuPont.

Product Notes

Notes:

History

Update and Revision:

Revision Number: 0.303 Revision Date: 12-20-2021

Variants

ltem #	Color	UPC
6320UJ 0021000	Red	612825175759

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multi-Conductor Cables category:

Click to view products by Belden manufacturer:

Other Similar products are found below :

8916-GRY-100 8917-BLK-100 8918-GRN/YEL-100 8920-BRN-1000 8920-RED-1000 89907-LT-DEC/GRY-500 CR3909-000 CR3927-000 01342.35T.01 01364.35T.01 CS2885-000 CS8782-000 CS9912-000 6200UE-NAT-U1000 CTC-0062-20-9/5-9 CTC-0062-22-9/5-9 6304FE-877-U500 6309UE-877-1000 6320UE-NAT-U1000 644833-000 6502FE 8771000 6504UE-877-U1000 CW9530-000 CX6543-000 CXA-0066-20-4-9CS2973 CXA-0078-16-1-9CS2405 CXA-0078-22-4-9CS2405 CXA-0078-24-4-9CS2405 CXA-0140-16-6/9-9CS2405 CY0660-000 720451-000 730859-000 MCC-USB-4-250 752687-000 768146-000 773159-000 7934A-BLK-1000 8125-CHR-100 8164-CHR-1000 820457-000 8205-CHR-1000 8240-BLK-U1000 82723-NAT-1000 82907-NAT-500 83003-YEL-500 83005-WHT-500 83006-DK-GRN-100 83008-WHT-1000 83009-BLK-100 83009-VIO-100